

EASTMAN

MATERIAL SAFETY DATA SHEET

Revision Date: 01/11/2002
MSDSUSA/ANSI/EN/150000049582/Version 2.0
0030368606/0000003462

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	"PICCO" 1104 Hydrocarbon Resin
Product Identification Number(s)	P7519501
Manufacturer/Supplier	Eastman Chemical Company, Kingsport, Tennessee 37662
MSDS Prepared by	Eastman Product Safety and Stewardship
Chemical Name	not applicable
Synonym(s)	800233
Molecular Formula	not applicable
Molecular Weight	not applicable
Product Use	industrial chemical
OSHA Status	nonhazardous

For emergency health, safety & environmental information, call 800-EASTMAN.

For emergency transportation information, call CHEMTREC at 800-424-9300 or call 800-EASTMAN.

2. COMPOSITION INFORMATION ON INGREDIENTS

(Typical composition is given, and it may vary. A certificate of analysis can be provided.)

Weight %	Component	CAS Registry No.
98 - 100%	hydrocarbon resin	proprietary
0 - 2%	residual additives, modifiers, colorants, reactants, and/or impurities	not applicable

3. HAZARDS IDENTIFICATION

CAUTION!
MOLTEN MATERIAL WILL PRODUCE THERMAL BURNS

HMIS® Hazard Ratings: Health - 1, Flammability -1, Chemical Reactivity - 0

NOTE: HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

4. FIRST-AID MEASURES

Inhalation: If symptomatic, move to fresh air. Get medical attention if symptoms persist.
Eyes: If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention immediately.
Skin: If burned by contact with molten material, cool as quickly as possible. Do not peel material from skin. Get medical attention.
Ingestion: Seek medical advice.
Note to Physicians: Burns should be treated as thermal burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.

©COPYRIGHT 2001 BY EASTMAN CHEMICAL COMPANY

Visit our website at www.EASTMAN.com

MARKETED BY
HARWICK STANDARD
DISTRIBUTION CORPORATION
60 S. Selberling Street • Akron, Ohio 44305

EASTMAN

MATERIAL SAFETY DATA SHEET

Revision Date: 01/11/2002
MSDSUSA/ANSI/EN/150000049582/Version 2.0
0030368606/0000003462

5. FIRE FIGHTING MEASURES

Extinguishing Media: water spray, dry chemical

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Hazardous Combustion Products: carbon dioxide, carbon monoxide

Unusual Fire and Explosion Hazards: Powdered material may form explosive dust-air mixtures.

6. ACCIDENTAL RELEASE MEASURES

Sweep or scoop up and remove.

7. HANDLING AND STORAGE

Personal Precautionary Measures: Avoid contact with molten material.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials. Minimize dust generation and accumulation. In the United States of America, refer to NFPA® Pamphlet No. 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries."

Storage: Keep container closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Country specific exposure limits have not been established or are not applicable unless listed below.

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances such as poorly ventilated spaces, mechanical generation of dusts, heating, drying, etc.

Respiratory Protection: If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: dust, organic vapor

Eye Protection: Wear a face shield when working with molten material.

Skin Protection: When material is heated, wear gloves to protect against thermal burns.

Recommended Decontamination Facilities: eye bath, washing facilities

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: solid (flake)

Color: dark

Odor: hydrocarbon

Specific Gravity: 1.05

Softening Point: 95 - 105 °C

Solubility in Water: negligible

Flash Point: 204.44 °C (method unspecified)

EASTMAN

MATERIAL SAFETY DATA SHEET

Revision Date: 01/11/2002
MSDSUSA/ANSI/EN/150000049582/Version 2.0
0030368606/0000003462

Thermal Decomposition Temperature: Thermal stability not tested. Low stability hazard expected at normal operating temperatures.

10. STABILITY AND REACTIVITY

Stability: Stable.
Incompatibility: Material reacts with strong oxidizing agents.
Hazardous Polymerization: will not occur

11. TOXICOLOGICAL INFORMATION

Toxicity data are not available unless listed below.

12. ECOLOGICAL INFORMATION

This material has not been tested for environmental effects.

13. DISPOSAL CONSIDERATIONS

Discharge, treatment, or disposal may be subject to national, state, or local laws. Incinerate.

14. TRANSPORT INFORMATION

Marine pollutant components: none unless listed below

DOT (USA): Class not regulated

ICAO Status: Class not regulated

IMDG Status: Class not regulated

15. REGULATORY INFORMATION

WHMIS (Canada) Status: noncontrolled
SARA 313: none, unless listed below

Carcinogenicity Classification (components present at 0.1% or more): none, unless listed below

EASTMAN

MATERIAL SAFETY DATA SHEET

Revision Date: 01/11/2002
MSDSUSA/ANSI/EN/150000049582/Version 2.0
0030368606/0000003462

TSCA (US Toxic Substances Control Act): All components of this product are listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act): All components of this product are listed on the DSL. Any impurities present in this product are exempt from listing.

EINECS (European Inventory of Existing Commercial Chemical Substances): All components of this product are listed on EINECS. Any polymer intentionally present in this product has regulatory clearance under Directives of the European Union.

AICS / NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme): All components of this product are listed on AICS or otherwise comply with NICNAS.

ECL (Korean Toxic Substances Control Act): All components of this product are listed on the Korean inventory or otherwise comply with the Korean Toxic Substances Control Act.

16. OTHER INFORMATION

For other information, call your Eastman representative or the Eastman operator at 423-229-2000 (USA).

The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment.