

MATERIAL SAFETY DATA SHEET

Ferro Corporation, Polymer Additives Division Walton Hills Operation 7050 Krick Road Walton Hills, Ohio 44146-4494 USA

Emergency telephone number

CHEMTREC: 1-800-424-9300

Plant Number: 1-216-750-6708

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name:

Therm-Chek® RC 154L

Date of Preparation: 07/21/2005

Chemical Family:

Polymer Additive

Chemical Name:

Barium, Zinc Complex Mixture

CAS-No.:

Mixture

Product code: 1115191

2. HAZARD IDENTIFICATION

Emergency Overview

Caution

May cause eye/skin irritation. Avoid contact with the skin and the eyes.

NFPA 704

Colour:

Dark amber

Health:

1

Physical state:

Liquid

Fire: Instability: 1 0

Odour:

Mild

Potential Health Effects

Principle routes of exposure: Eye contact. Skin contact. Inhalation.

Eve contact: May cause slight irritation.

Skin contact: Prolonged skin contact may cause skin irritation and/or dermatitis.

Inhalation: May cause irritation of respiratory tract.

Ingestion: May irritate digestive tract.

| 。 | 3. COMPOSITION/INFORM | ATION ON INGREDIENTS |
|-----------------------------|-----------------------|----------------------|
| Components | CAS Number | Weight % |
| Barium compounds | | 10 - 20% |
| Zinc compounds | | 5 - 10% |
| Petroleum based hydrocarbon | | 1 - 5% |

The specific chemical identities are being withheld as a trade secret (29CFR1910.1200).

This material contains organo phosphorous compounds which may decompose from hydrolysis to produce phenol, aliphatic alcohol, and phosphoric acid.

4. FIRST AID MEASURES

Eye contact: Rinse immediately with plenty of water, also under the eyelids. Get medical attention if irritation develops.

Skin contact: Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms persist, call a physician.

Ingestion: Drink plenty of water. Consult a physician if necessary. Do not induce vomiting without medical advice.

Product name: Therm-Chek® RC 154L

MARKETED BY HARWICK STANDARD DISTRIBUTION CORPORATION

60 S. Seiberling Street • Akron, Ohio 44305

Page 1 of 4

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash point: 112 °C (234°F) Method: PMCC

Suitable extinguishing media: Use dry chemical, CO2, water spray or "alcohol" foam.

Hazardous decomposition products: Thermal decomposition can lead to release of irritating gases and vapors.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, NIOSH (approved or equivalent) and full protective gear.

Unusual hazards: Material may change or decompose on exposure to moisture.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Evacuate area of all unnecessary personnel. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up: Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Dispose of promptly. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage: Keep container tightly closed in a dry and well-ventilated place. Keep containers dry and tightly closed to avoid moisture absorption and contamination.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits:

| Components | OSHA | ACGIH | |
|-----------------------------|--|--|--|
| Barium compounds, as Ba | 0.5 mg/m³ TWA | 0.5 mg/m³ TWA | |
| Petroleum based hydrocarbon | 5 mg/m ³ TWA (mineral oil mist) | 5 mg/m ³ TWA (mineral oil mist) | |

Engineering measures: Ensure adequate ventilation, especially in confined areas.

Eye protection: Safety glasses with side-shields.

Skin and body protection: Lightweight protective clothing.

Hand protection: Impervious gloves.

Respiratory protection: Use NIOSH approved respirator when ventilation is inadequate.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Ensure that eyewash stations and safety showers are proximal to the work-station location. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Colour:

Physical state:

Dark amber

Liquid

No data available

Molecular weight:

No data available

Vapor pressure (mmHg): Water solubility (mg/l):

No data available

Insoluble

Appearance:

Clear Mild

Odour:

Boiling point/range (°C):

No data available 1.083

Specific gravity (Water =1):

Evaporation rate (Water =1):

> 1.00 No data available

VOC content (%)

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Polymerization: Will not occur.

Hazardous decomposition products: None under normal use. Possible decomposition products from hydrolysis:. phenol, aliphatic

alcohol, phosphoric acid.

Materials to avoid: Strong oxidizing agents. Strong acids and strong bases. Water.

Conditions to avoid: Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: No data is available on the product itself

Target Organ Effects: Barium compound: Heart, gastrointestinal tract.

12. ECOLOGICAL INFORMATION

Aquatic toxicity: Not determined

Persistence and degradability: Not determined

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: Waste must be disposed of in accordance with federal, state and local environmental control regulations. Where possible recycling is preferred to disposal or incineration.

14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated.

TDG (Canada)

Proper shipping name: Not regulated.

15. REGULATORY INFORMATION

U.S. Regulations:

Not subject to TSCA 12(b) Export Notification

| Components | SARA 313: | | |
|-----------------------------------|--|--|--|
| Barium compounds (10 - 20%) | 1.0% de minimis concentration (Chemical Category N040) | | |
| Barium compounds, as Ba (5 - 10%) | 1.0% de minimis concentration (Chemical Category N040) | | |
| Zinc compounds (5 - 10%) | 1.0% de minimis concentration (Chemical Category N982) | | |
| Zinc compounds, as Zn (1 - 5%) | 1.0% de minimis concentration (Chemical Category N982) | | |

State Regulations

This product or its ingredients have been evaluated for New Jersey, Pennsylvania, and California Prop 65 supplier notification requirements. Substances that are subject to notification requirements, if any, are listed below.

| Components | NJRTK: | PARTK: | Cal Prop65: |
|---------------------|-------------|--------|-------------|
| Barium compounds | 2146 (1.0%) | Listed | N/A |
| Zinc compounds | 3012 | Listed | N/A |
| Triphenyl phosphite | N/A | N/A | N/A |
| Barium carbonate | sn 0180 | Listed | N/A |
| Benzoic acid | sn 0209 | Listed | N/A |

Canadian WHMIS

WHMIS hazard class: D2B Toxic materials.

Components

Triphenyl phosphite Barium carbonate Benzoic acid WHMIS Ingredient Disclosure:

1% 0.1% 1%

International Inventories

TSCA 8(b): Listed or exempt.
Canadian DSL: Listed or exempt.
EINECS: Listed or exempt.
Phillipines (PICCS): Not listed.
Japan (ENCS): Not listed.
Korea (KECL): Listed.
China (IECS): Listed.
Australia (AICS): Listed.

16. OTHER INFORMATION

For Industrial Use Only

HMIS Health: 1 Fire: 1

Physical hazard: 0

PPE: B

Prepared by: Ferro Technical Center

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.

End of Safety Data Sheet