SAFETY DATA SHEET



1. Identification

Product identifier Therm-Chek® SP121

Other means of identification

Product code 1036516, 1036459, 1035557

Recommended use Modifier.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Valtris Specialty Chemicals

Address 7050 Krick Road

Walton Hills, OH 44146

United States

Telephone Customer Service (216) 875-7284

Website www.valtris.com

E-mail sdsquestions@valtris.com
Contact person Valtris Technical Center
Emergency phone number CHEMTREC: 1-800-424-9300

CHEMTREC Contract No: 717960

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Serious eye damage/eye irritation Category 1
Specific target organ toxicity, repeated Category 1 (lung)

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazaro

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed. Causes serious eye damage. Causes damage to organs (lung) through

prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting

Category 3

effects.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Avoid release to the environment. Wear eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Immediately call a poison center/doctor.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: Therm-Chek® SP121 SDS US

1036516, 1036459, 1035557 Version #: 02 Revision date: 06-06-2016 Issue date: 05-20-2015

78.82% of the mixture consists of component(s) of unknown acute oral toxicity. 89.59% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 89.59% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Barium compounds		*	10 - < 20
Zinc compounds		*	10 - < 20
Organic solvents		*	5 - < 10
Organophosphorous compound		*	5 - < 10
Carboxylic acid		*	3 - < 5
Phenol		108-95-2	3 - < 5
Glycol ether		*	1 - < 3

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

General information

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Discomfort in the chest. Shortness of breath. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Move containers from fire area if you can do so without risk.

During fire, gases hazardous to health may be formed.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Therm-Chek® SP121

Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get this material in contact with eyes. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Use care in handling/storage.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

0.5 mg/m3

100 mg/m3

60 mg/m3 15.6 ppm

19 mg/m3 5 ppm

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Barium compounds	PEL	0.5 mg/m3	
Phenol (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	Form
Barium compounds	TWA	0.5 mg/m3	
Glycol ether	TWA	10 ppm	Inhalable fraction and vapor.
Phenol (CAS 108-95-2)	TWA	5 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	

Biological limit values

Barium compounds

Phenol (CAS 108-95-2)

Organic solvents

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Phenol (CAS 108-95-2)	250 mg/g	Phenol with hydrolysis	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

TWA

TWA

TWA

Ceiling

US - Minnesota Haz Subs: Skin designation applies

Phenol (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

1036516, 1036459, 1035557 Version #: 02 Revision date: 06-06-2016 Issue date: 05-20-2015

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Phenol (CAS 108-95-2) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

evewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

Wear suitable protective clothing. Use of an impervious apron is recommended. Other

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Amber Odor Slight.

Odor threshold Not available. Not available.

77 °F (25 °C) estimated Melting point/freezing point Initial boiling point and boiling 347 °F (175 °C) estimated

range

Flash point 219.2 °F (104.0 °C) Pensky-Martens Closed Cup

Evaporation rate < 1

Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Flammability limit - lower 0.7 % estimated

Flammability limit - upper

5 % estimated

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

0.06 hPa estimated Vapor pressure

Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

410 °F (210 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 1.02 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Oxidizing properties Not oxidizing.

Percent volatile 1.4 % estimated

Specific gravity 1.07

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation.

Skin contactNo adverse effects due to skin contact are expected.

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and

toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Discomfort in the

chest. Shortness of breath.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components	Species	Test Results	
Carboxylic acid			
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 5000 mg/kg	
Oral			
LD50	Cat	2000 mg/kg	
	Dog	2000 mg/kg	
	Mouse	1940 mg/kg	
	Rat	1700 mg/kg	
Glycol ether			
<u>Acute</u>			
Dermal			
LD50	Rabbit	2700 mg/kg	
Oral			
LD50	Guinea pig	2000 mg/kg	
	Mouse	2400 mg/kg	
	Rabbit	2200 mg/kg	
	Rat	4500 mg/kg	

Material name: Therm-Chek® SP121

Components Species Test Results

Organophosphorous compound

<u>Acute</u>

Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LD50 Rat 6.7 mg/l

Oral LD50

Mouse 1330 mg/kg

Rat 1600 mg/kg

Phenol (CAS 108-95-2)

Acute

Dermal

LD50 Rabbit 850 mg/kg

Rat 669 mg/kg

Oral

LD50 Cat 0.1 g/kg

 Dog
 0.5 g/kg

 Mouse
 270 mg/kg

 Rat
 317 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Phenol (CAS 108-95-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ

toxicity - single exposure

Not classified.

Specific target organ

toxicity - repeated

Causes damage to organs (lung) through prolonged or repeated exposure.

exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components Species Test Results

Carboxylic acid

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 180 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Components		Species	Test Results
Glycol ether			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	1300 mg/l, 96 hours
Organic solvents			
Aquatic			
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Phenol (CAS 108-95-2))		
Aquatic			
Crustacea	EC50	Water flea (Daphnia obtusa)	4.7 - 6.4 mg/l, 48 hours
Fish	LC50	Asiatic knifefish (Notopterus notopterus)	8 - 8.25 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Carboxylic acid 1.87 Glycol ether 0.56 Phenol 1.46

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Barium compounds (CAS *)

Carboxylic acid (CAS *)

Listed.

Listed.

Glycol ether (CAS *)

Organophosphorous compound (CAS *)

Phenol (CAS 108-95-2)

Zinc compounds (CAS *)

Listed.

Listed.

Listed.

SARA 304 Emergency release notification

Phenol (CAS 108-95-2) 1000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Phenol	108-95-2	1000		500 lbs	10000 lbs

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
BARIUM COMPOUNDS [EXCEPT BASO4]	*	10 - < 20	
ZINC COMPOUNDS	*	10 - < 20	
PHENOL	108-95-2	3 - < 5	
CERTAIN GLYCOL ETHERS	*	1 - < 3	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Glycol ether (CAS *)

Organophosphorous compound (CAS *)

Phenol (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Phenol (CAS 108-95-2) Low priority

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. Massachusetts RTK - Substance List

Carboxylic acid (CAS *)

Organic solvents (CAS *)

Phenol (CAS 108-95-2)

US. New Jersey Worker and Community Right-to-Know Act

Barium compounds (CAS *)

Carboxylic acid (CAS *)

Glycol ether (CAS *)

Organic solvents (CAS *)

Phenol (CAS 108-95-2)

Zinc compounds (CAS^{*})

US. Pennsylvania Worker and Community Right-to-Know Law

Carboxylic acid (CAS *)

Glycol ether (CAS *)

Organic solvents (CAS *)

Phenol (CAS 108-95-2)

US. Rhode Island RTK

Barium compounds (CAS *)

Material name: Therm-Chek® SP121 1036516, 1036459, 1035557 Version #: 02 Revision date: 06-06-2016 Issue date: 05-20-2015 SDS US

Carboxylic acid (CAS *) Glycol ether (CAS *)

Organophosphorous compound (CAS *)

Phenol (CAS 108-95-2) Zinc compounds (CAS *)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region

No
Yes
No
Yes
No
Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Inventory name

05-20-2015 Issue date **Revision date** 06-06-2016

Version # 02

Valtris Specialty Chemicals cannot anticipate all conditions under which this information and its Disclaimer

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

1036516, 1036459, 1035557 Version #: 02 Revision date: 06-06-2016 Issue date: 05-20-2015

On inventory (yes/no)*