

DuPont Dow Elastomers L. L. C.
Material Safety Data Sheet

Page 1

DEVELOPMENTAL CHLORINATED POLYETHYLENE ALL IN SYNONYM LIST ELX107
ELX107 Revised 19-MAR-1999 Printed 19-JAN-2001

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Tradenames and Synonyms

TYR2500.00P
TYR2500.01P
TYR2500.02P
TYR3054.00P
TYR3300.00P
TYR3600.00P
TYR3600.01P
TYR4205.00
TYR7000.00
TYR6002.00G
TYR9001.01
TYR9236.00P
TYX9001.01
CHLORINATED POLYETHYLENE, CPE

#

Company Identification

MANUFACTURER/DISTRIBUTOR

DuPont Dow Elastomers L. L. C.
Bellevue Park Corporate Center
300 Bellevue Parkway
Wilmington, Delaware 19809

PHONE NUMBERS

Product Information : 1-800-441-7515
Transport Emergency : CHEMTREC 1-800-424-9300
Medical Emergency : 1-800-441-3637

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
CHLORINATED POLYETHYLENE	64754-90-1	92-100
TALC, CONTAINING NO ASBESTOS FIBERS	14807-96-6	0-6
CALCIUM STEARATE	1592-23-0	<2.5

Components (Remarks)

Material is not known to contain Toxic Chemicals under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

MARKETED BY

HARWICK STANDARD
DISTRIBUTION CORPORATION

60 S. Seiberling Street • Akron, Ohio 44305

HAZARDS IDENTIFICATION
-----**Potential Health Effects****ADDITIONAL HEALTH EFFECTS****CHLORINATED POLYOLEFIN****ACUTE OR IMMEDIATE EFFECTS : ROUTES OF ENTRY AND SYMPTOMS**

INGESTION Not a probable route of exposure. Single dose oral LD-50 has not been determined. Single dose oral toxicity is believed to be very low.

SKIN Skin contact, especially with hot polymer, may cause skin irritation in some sensitive people resulting in redness, itching and in extreme cases, blistering. Avoid contact with hot polymer which may give thermal burns.

EYE Polymer chips or dust in the eye may cause mechanical damage including scratching of the cornea.

INHALATION Vapors released during processing may be composed of hydrogen chloride and possibly carbon monoxide. These gases are evolved, they will cause tearing and burning of the eyes. The vapors will also cause irritation to the upper respiratory tract which results in a sore throat and coughing in severe cases with shortness of breath.

TALC

Short-term over-exposure by inhalation to Talc may cause irritation of the nose, throat and lungs with cough, difficulty breathing or shortness of breath. Long-term over-exposure may lead to chronic lung disease with impaired lung function and abnormal chest x-rays.

Increased susceptibility to the effects of Talc may be observed in persons with pre-existing disease of the lungs.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

ELX107

DuPont Dow Elastomers L. L. C.
Material Safety Data Sheet

Page 3

FIRST AID MEASURES

First Aid**INHALATION**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.
If molten material gets on skin, cool rapidly with cold water. Do not attempt to remove material from skin. Obtain medical treatment for thermal burn.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

Not a probable route. However, in case of accidental ingestion, call a physician.

FIRE FIGHTING MEASURES

Flammable Properties

Like most organic powders or crystals, under severe dusting conditions, this material may form explosive mixtures in air.

Fire and Explosion Hazards:**UNUSUAL FIRE, EXPLOSION HAZARDS**

Solid polymer can be combusted only with difficulty. Hydrogen chloride is a decomposition/combustion product.

HAZARDOUS COMBUSTION PRODUCTS: Hydrogen chloride, carbon monoxide, organic acids, aldehydes, alcohols.

Extinguishing Media

Water Fog, Foam, Dry Chemical, CO2

Fire Fighting Instructions

Use self-contained breathing apparatus and protective clothing to avoid exposure to hydrogen chloride and other fumes.

ELX107

DuPont Dow Elastomers L. L. C.
Material Safety Data Sheet

Page 4

ACCIDENTAL RELEASE MEASURES
-----**Safeguards (Personnel)**

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Spill Clean Up

Shovel or sweep up.

HANDLING AND STORAGE
-----**Handling (Personnel)**

See FIRST AID and PERSONAL PROTECTIVE EQUIPMENT SECTIONS

Storage

Store in a cool, dry place

EXPOSURE CONTROLS/PERSONAL PROTECTION
-----**Engineering Controls**

Use sufficient ventilation to keep employee exposure below recommended limits. Use static controls. Static charges can build up and ignite dust or solvent laden atmospheres.

Personal Protective Equipment**EYE/FACE PROTECTION**

Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye and face contact due to splashing or spraying of molten material. A full face mask respirator provides protection from eye irritation.

RESPIRATORS

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge with a dust/mist filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

PROTECTIVE CLOTHING

ELX107

DuPont Dow Elastomers L. L. C.
Material Safety Data Sheet

Page 5

(EXPOSURE CONTROLS/PERSONAL PROTECTION - Continued)

If there is potential contact with hot/molten material, wear heat resistant clothing and footwear.

Exposure Guidelines

Applicable Exposure Limits

TALC, CONTAINING NO ASBESTOS FIBERS

PEL (OSHA)	:	Respirable dust, 1/2*(80 mg/m ³ / % SiO ₂) as 8 Hr TWA
TLV (ACGIH)	:	2 mg/m ³ , respirable dust, 8 Hr. TWA, A4
AEL * (DuPont)	:	0.5 mg/m ³ , 8 & 12 Hr. TWA respirable dust

CALCIUM STEARATE

PEL (OSHA)	:	None Established
TLV (ACGIH)	:	10 mg/m ³ , total dust, 8 Hr. TWA A4
AEL * (DuPont)	:	None Established

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Melting Point	:	80-120 C (176-248 F)
Solubility in Water	:	Negligible
Odor	:	No odor
Form	:	Powder
Color	:	Off-white
Specific Gravity	:	1.25-1.8

STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and storage conditions.

Conditions to Avoid

Avoid open flames and high temperatures.

Incompatibility with Other Materials

None reasonably foreseeable.

ELX107

DuPont Dow Elastomers L. L. C.
Material Safety Data Sheet

Page 6

(STABILITY AND REACTIVITY - Continued)

Decomposition

Hazardous gases or vapors can be released, including carbon monoxide, hydrogen chloride (HCl), hydrocarbon oxidation products including organic acids, aldehydes and alcohols.

Polymerization

Polymerization will not occur.

TOXICOLOGICAL INFORMATION
-----**Animal Data****TALC****Talc**

Oral LD50: 920 mg/kg in rats
Inhalation 5 hour ALC: > 22 mg/L in rats

Long-term exposure by ingestion to Talc caused no significant decrease in life span.

A single exposure by inhalation to high doses of Talc caused irregular respiration and lacrimation but no evidence of an inflammatory reaction. Repeated exposure caused no adverse effects on survival or histological changes. Long-term exposure in rats caused chronic inflammation, impaired pulmonary function and histopathological changes of the lungs.

One lifetime inhalation study reports an increased incidence of lung and adrenal tumors in rats exposed to Talc. The lung tumors and chronic inflammation occurred at dust levels which overwhelmed the animals lung clearance mechanism and, therefore, are of questionable biological relevance for man. The adrenal tumors are unlikely to be a direct effect of Talc exposure and are of questionable relevance. No increases in tumors were observed in mice. Talc has not caused developmental toxicity in animals. No animal data are available to define the reproductive toxicity of Talc. Tests have shown that Talc does not cause genetic damage in bacterial or mammalian cell cultures, or in animals. Animal data indicate that Talc does not cause permanent genetic damage in reproductive cells of mammals (does not cause heritable genetic damage).

ELX107

DuPont Dow Elastomers L. L. C.
Material Safety Data Sheet

Page

ECOLOGICAL INFORMATION
-----**Ecotoxicological Information****AQUATIC TOXICITY:**

No information is available. Toxicity is expected to be low based on insolubility in water.

DISPOSAL CONSIDERATIONS
-----**Waste Disposal**

Preferred options for disposal are (1) recycling, (2) incineration with energy recovery, and (3) landfill. The high fuel value of this product makes option 2 very desirable for material that cannot be recycled, but incinerator must be capable of scrubbing out acidic combustion products. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

TRANSPORTATION INFORMATION
-----**Shipping Information****DOT**

Proper Shipping Name : Not regulated.

REGULATORY INFORMATION
-----**U.S. Federal Regulations**

TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes

State Regulations (U.S.)**STATE RIGHT-TO-KNOW**

No substances on the state hazardous substances list, for the states indicated below, are used in the manufacture of products on this Material Safety Data Sheet, with the exceptions indicated.

SUBSTANCES ON THE PENNSYLVANIA HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 1 % OR MORE (0.01% FOR SPECIAL HAZARDOUS SUBSTANCES)- Talc.

WARNING - SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM- None known.

SUBSTANCES ON THE NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE LIST PRESENT AT A CONCENTRATION OF 1% OR MORE (0.1% FOR SUBSTANCES IDENTIFIED AS CARCINOGENS, MUTAGENS OR TERATOGENS)- Talc.

ELX107

DuPont Dow Elastomers L. L. C.
Material Safety Data Sheet

Page 8

OTHER INFORMATION

Additional Information

MEDICAL USE: CAUTION: Do not use in medical applications involving permanent implantation in the human body. For other medical applications see DuPont Dow Elastomers Medical Application Policy (H-69237).

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for MSDS : G. W. WORTHAM
Address : DuPont Dow Elastomers L. L. C.
CHESTNUT RUN PLAZA 713
WILMINGTON, DE 19880-0713
Telephone : 302-999-2319

Indicates updated section

End of MSDS