

SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY*

Product name: PARALOID™ K-415 Processing Aid Issue Date: 04/17/2015 Print Date: 08/16/2016

THE DOW CHEMICAL COMPANY* encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: PARALOID™ K-415 Processing Aid

Recommended use of the chemical and restrictions on use

Identified uses: Plastics Additive

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY*
Agent for Rohm and Haas Chemicals LLC
100 INDEPENDENCE MALL WEST
PHILADELPHIA PA 19106-2399
UNITED STATES

Customer Information Number: 215-592-3000

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 424 9300 **Local Emergency Contact:** 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Combustible dust

Label elements

Signal word: WARNING!

Hazards

May form combustible dust concentrations in air

Precautionary statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Take precautionary measures against static discharge.

Other hazards

no data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Acrylic copolymer

This product is a mixture.

| Component | CASRN | Concentration |
|------------------------------|--------------|---------------|
| | | |
| P(BA/BMA/MMA) | 25322-99-0 | 80.0 - 85.0 % |
| P(BA/MMA) | 25852-37-3 | 14.0 - 17.0 % |
| Alkylaryl sulfonate | Trade Secret | 1.0 - 2.0 % |
| Individual residual monomers | Not Required | < 0.05 % |

4. FIRST AID MEASURES

Description of first aid measures

Inhalation: Move to fresh air.

Skin contact: Wash with water and soap as a precaution. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.

Eye contact: Rinse with water. If eye irritation persists, consult a specialist.

Ingestion: Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Consult a physician if necessary.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Treatment should be directed at preventing absorption, administering to symptoms (if they occur), and providing supportive therapy.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide (CO2) Dry chemical Water spray

Unsuitable extinguishing media: no data available

Page 2 of 11

Product name: PARALOID™ K-415 Processing Aid

Issue Date: 04/17/2015

Special hazards arising from the substance or mixture Hazardous combustion products: no data available

Unusual Fire and Explosion Hazards: Material as sold is combustible; burns vigorously with intense heat. Dusts at sufficient concentrations can form explosive mixtures with air. DO NOT use a solid stream of water. A solid stream of water directed at this material may create a potentially explosive airborne dust mixture.

Advice for firefighters

Fire Fighting Procedures: no data available

Special protective equipment for firefighters: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Wear compatible, chemically resistant gloves. Use personal protective equipment. Avoid breathing dust. Material can create slippery conditions. Remove all sources of ignition. Ensure adequate ventilation.

Environmental precautions: CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods and materials for containment and cleaning up: Sweep up and shovel into suitable containers for disposal. Use water spray to keep dusting to a minimum.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not breathe dust. Do not breathe vapors, mist or gas. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat and sources of ignition. Ground all metal containers during storage and handling. Ensure adequate ventilation. Keep container tightly closed.

Conditions for safe storage: Store at room temperature in the original container. Keep away from heat and sources of ignition. Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Avoid all ignition sources. This material is not hazardous under normal storage conditions. However, all materials of this type release some monomer vapors or gases when stored for prolonged periods at elevated temperatures.

Other data: Avoid high concentrations of dust in air and accumulation of dust on equipment. An airborne dust of this material can create a dust explosion. When handling and processing this material local exhaust ventilation may be required to control dust and reduce exposure to vapors. To prevent dust explosions employ bonding and grounding for operations capable of generating static electricity. Protect all equipment from explosions by following the guidelines in NFPA-68 and NFPA-69. For electrical equipment follow local codes and electrical classification NFPA-70 (the National Electrical Code), class II, division 2, group G.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

| | Regulation | Type of listing | Value/Notation |
|---------|---------------|-----------------|----------------|
| Product | Rohm and Haas | TWA Respirable | 1 mg/m3 |
| | | fraction. | |

Exposure controls

Engineering controls: Use explosion-proof local exhaust ventilation with a minimum capture velocity of 150 ft/min (0.75 m/sec) at the point of dust or mist evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility.

Individual protection measures

Eye/face protection: Safety glasses with side-shields Eye protection worn must be compatible with respiratory protection system employed.

Skin protection

Hand protection: For prolonged or repeated contact use protective gloves. **Respiratory protection:** A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. When dusty conditions are encountered, wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) N95 filters. If oil mist is present, use R95 or P95 filters.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state powder

Color Free-flowing white
Odor Pungent, sweet odor
Odor Threshold no data available
pH Not applicable

Melting point/range 132.00 - 149.00 °C (269.60 - 300.20 °F)

Freezing point no data available
Boiling point (760 mmHg) Not applicable
Flash point no data available
Evaporation Rate (Butyl Acetate Not applicable

= 1)

Flammability (solid, gas) May form combustible dust concentrations in air

Lower explosion limitno data availableUpper explosion limitno data available

Vapor PressureNot applicableRelative Vapor Density (air = 1)Not applicableRelative Density (water = 1)1.0000 - 1.2000

Water solubility insoluble

Partition coefficient: n- no data available

octanol/water

Auto-ignition temperature 400.00 °C (752.00 °F)

Decomposition temperatureno data availableDynamic ViscosityNot applicableKinematic Viscosityno data availableExplosive propertiesno data availableOxidizing propertiesno data availableMolecular weightno data available

Percent volatility 1.00 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: no data available

Chemical stability: no data available

Possibility of hazardous reactions: None known.

Product will not undergo polymerization.

Stable

Conditions to avoid: no data available

Incompatible materials: Prolonged contact with acids, alkalies and strong oxidizing agents may attack or dissolve the polymer.

Hazardous decomposition products: Heating above the decomposition temperature will release acrylic monomers.

11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Acute toxicity

Acute oral toxicity

LD50, Rat, female, > 2,000 mg/kg

Acute dermal toxicity

LD50, Rat, > 2,000 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 3.4 mg/l The LC50 value is greater than the Maximum Attainable Concentration.

Skin corrosion/irritation

No skin irritation

Serious eye damage/eye irritation

slight irritation

Sensitization

Product test data not available.

Specific Target Organ Systemic Toxicity (Single Exposure)

Product test data not available.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

A 13-week inhalation study in rats of a compositionally similar acrylic powder showed inflammatory effects in the lung at concentrations of 6 mg/m3 for 6 hours per day, 5 days per week. These findings were consistent with high concentration exposure effects reported for other non-soluble dusts. Maintaining airborne dust concentrations within the recommended exposure limit is not expected to produce adverse effects within the lung.

Carcinogenicity

Product test data not available.

Teratogenicity

Product test data not available.

Reproductive toxicity

Product test data not available.

Mutagenicity

Product test data not available.

Aspiration Hazard

Product test data not available.

Additional information

No data are available for this material. The information shown is based on profiles of compositionally similar materials.

COMPONENTS INFLUENCING TOXICOLOGY:

P(BA/BMA/MMA)

Sensitization

For skin sensitization:

For this family of materials, sensitization studies done in guinea pigs have been negative.

For respiratory sensitization:

No relevant data found.

Carcinogenicity

No relevant data found.

Teratogenicity

No relevant data found.

Reproductive toxicity

No relevant data found.

Mutagenicity

In vitro genetic toxicity studies were negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

P(BA/MMA)

Sensitization

No relevant information found.

For respiratory sensitization:

No relevant information found.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Alkylaryl sulfonate

Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Carcinogenicity

Did not cause cancer in laboratory animals.

Teratogenicity

For similar material(s): Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

Reproductive toxicity

For similar material(s): In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

Mutagenicity

Based on information for a similar material: In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

General Information

There is no data available for this product.

Toxicity

P(BA/BMA/MMA)

Acute toxicity to fish

For this family of materials:

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For this family of materials:

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates

For this family of materials:

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

P(BA/MMA)

Acute toxicity to fish

No relevant information found.

Alkvlarvl sulfonate

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Lepomis macrochirus (Bluegill sunfish), static test, 96 Hour, 6.81 mg/l

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 6.2 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), static test, 48 Hour, 1.64 mg/l, Other guidelines

Acute toxicity to algae/aguatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 21 d, Growth inhibition (cell density reduction), 100 mg/l

Toxicity to bacteria

Based on analogy.

EC50, activated sludge, static test, 0.5 Hour, Respiration rates., > 100 mg/l, activated sludge test (OECD 209)

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, survival, 0.65 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 28 d, > 1,000 mg/kg

Persistence and degradability

P(BA/BMA/MMA)

Biodegradability: Although the polymers are not biodegradable, they would likely be removed in biological wastewater treatment plants by adsorption to biosolids.

P(BA/MMA)

Biodegradability: No relevant information found.

Alkylaryl sulfonate

Biodegradability: Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability). Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Not applicable **Biodegradation:** < 70 % **Exposure time:** 28 d

Method: OECD Test Guideline 302B or Equivalent

10-day Window: Not applicable **Biodegradation:** < 60 % **Exposure time:** 20 d

Method: OECD Test Guideline 301D or Equivalent

Bioaccumulative potential

P(BA/BMA/MMA)

Bioaccumulation: No bioconcentration of the polymeric component is expected because of its high molecular weight. Latex dispersions will color water a milky white.

P(BA/MMA)

Bioaccumulation: No relevant data found.

Alkylaryl sulfonate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient:** n-octanol/water(log Pow): -2.68 at 20 °C estimated

Mobility in soil

P(BA/BMA/MMA)

No data available.

P(BA/MMA)

No relevant data found.

Alkylaryl sulfonate

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Place powder in air-tight bags. For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

Page 9 of 11

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Consult IMO regulations before transporting ocean bulk

Issue Date: 04/17/2015

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Chronic Health Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

HMIS

| Health | Flammability | Physical Hazard |
|--------|--------------|--------------------|
| 1* | 1 | 0 |

^{* =} Chronic Effects (See Hazards Identification)

Revision

Identification Number: 101078174 / 1001 / Issue Date: 04/17/2015 / Version: 1.2 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

| 9 | |
|---------------|------------------------------|
| Rohm and Haas | Rohm and Haas OEL's |
| TWA | Time Weighted Average (TWA): |

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY* urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.