# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: CALIFLUX GP®

Page 1 of 4

**HMIS DATA** 

H 1 F 1 R 0 PP

ATED A GARAGE	MIS Hazard Rating
INT FYX: SILL III	ALLO LISCALO MARINE
A - Estadoro	11 - C12-Land
4 = Extreme	
The Particular Control of the Particular Con	0 = Insignificant
	U — insignificant
2 = Moderate	
··· ··· ·· · · · · · · · · · · · · · ·	(= ) ( (0 )) ( (1) ((1)



### COMPANY NAME AND LOCATION - SECTION 1

COMPANY: Golden Bear Oil Specialties.

LOCATION: P.O. Box 5446, 1134 Manor Street, Oildale, CA 93388-5446.

EMERGENCY TELEPHONE NUMBER: (805) 393-7110.

TRANSPORTATION EMERGENCY: CHEMTREC (800) 424-9300 (U.S. and Canada).

### CHEMICAL AND PHYSICAL PROPERTIES - SECTION II

CHEMICAL NAME: Petroleum Hydrocarbon.

FORMULA: Not Applicable.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide and carbon dioxide from burning.

Oxides of nitrogen.

Oxides of sulfur.

FORM: Oily Liquid.

INCOMPATIBILITY (Keep away from):

Strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.

TOXIC AND HAZARDOUS INGREDIENTS:

EDIENTS: CAS NUMBER 64742-11-6

Heavy naphthenic extract (petroleum)

ODOR: No objectionable odor.

APPEARANCE: COLOR:

SPECIFIC GRAVITY (water = 1): 0.95 to 1.04.

BOILING POINT: Greater than 288°C (550°F).

MELTING POINT: Not applicable.

SOLUBILITY IN WATER (by weight %): 0.

VOLATILE (by weight %): Less than 0.01 at 25°C.

EVAPORATION RATE (water = 1): Less than 0.01.

VAPOR PRESSURE (mm Hg at 20°C): Less than 1.0.

VAPOR DENSITY (air = 1): No data available.

pH (as is): Not applicable.

STABILITY: Product is stable under normal conditions.

VISCOSITY (SUS at 100°F): Greater than or equal to 100.

OTHER PHYSICAL PROPERTIES: Viscosity greater than or equal to 18.6 cSt at 40°C.

MARKETED BY

HARWICK STANDARD

DISTRIBUTION CORPORATION
60 S. Seiberling Street · Akron, Ohio 44305

Akron · Chicago · Northeast · Southern · West Coast

# MATERIAL SAFETY DATA SHEET

The continues of

PRODUCT NAME: CALIFLUX GP®

Page 2 of 4

### FIRE AND EXPLOSION DATA - SECTION III

SPECIAL FIRE FIGHTING PROCEDURES: Avoid use of water.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Dense smoke. Fire fighters should wear an approved self-contained breathing apparatus.

FLASHPOINT (method used): Cleveland Open Cup - greater than 149°C (300°F).

FLAMMABLE LIMITS, %: No data available.

### **EXTINGUISHING AGENTS:**

Drychemical, Waterspray, CO, or Foam.

Water may cause frothing.

Water may be ineffective.

Closed containers exposed to fire may be cooled with water.

### HEALTH HAZARD DATA - SECTION IV

### PERMISSIBLE CONCENTRATIONS (air):

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m<sup>3</sup> for mineral oil mist (OSHA and ACGIH).

### CHRONIC EFFECTS OF OVEREXPOSURE:

Prolonged skin contact may cause irritation and under extreme conditions, skin cancer.

See COMMENTS section.

### **ACUTE TOXICOLOGICAL PROPERTIES:**

No data available.

#### **EMERGENCY FIRST AID PROCEDURES:**

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: Wash with soap and water.

Inhalation: Remove victim to fresh air.

If Swallowed: Contact a physician immediately.

ROUTES OF ENTRY: Ingestion and, if a mist is generated, inhalation.

TARGET ORGAN(S): Skin. Respiratory tract if a mist is generated (the respiratory tract may become irritated).

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Persons susceptible to dermatitis (skin rash) may aggravate their condition by skin contact with this product.

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: CALIFLUX GP®

Page 3 of 4

**2**1005

## SPECIAL PROTECTION INFORMATION - SECTION V

VENTILATION TYPE REQUIRED (local, mechanical, special): Local if necessary to maintain allowable PEL (permissible exposure limit) or TLV (threshold limit value).

RESPIRATORY PROTECTION (specify type): Use NIOSH/MSHA certified respirator with organic vapor cartridge if vapor concentration exceeds permissible exposure limit.

PROTECTIVE GLOVES: Oil resistant.

EYE PROTECTION: Chemical safety goggles and, if handled hot, full face shield.

OTHER PROTECTIVE EQUIPMENT: None.

#### HANDLING OF SPILLS OR LEAKS - SECTION VI

PROCEDURES FOR CLEAN-UP: In case of spill or leak absorb on an inert material such as earth, sand or vermiculite; sweep up and dispose of in accordance with federal, state and local regulations. If spilled into water, remove bulk of the product by skimming. If spilled into a navigable waterway and a film, sheen or discoloration of any water surface is noted, the spill must be reported to the National Response Center by calling (800) 424-8802.

WASTE DISPOSAL: Dispose of in accordance with all applicable federal, state and local regulations.

### SPECIAL PRECAUTIONS - SECTION VII

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Avoid prolonged or repeated contact with skin or breathing of vapors, mists or fumes. Launder contaminated clothing before reuse. Keep containers tightly closed. Avoid strong oxidizers. Eliminate all sources of ignition such as flames or sparks.

#### TRANSPORTATION DATA - SECTION VIII

D.O.T.: Regulated.

U.S. D.O.T. PROPER SHIPPING NAME: Elevated temperature liquid, n.o.s.(at or above 100°C (212°F) and below its flash point), (petroleum oil).

U.S. D.O.T. HAZARD CLASS: 9

ID NUMBER: UN 3257; PG III

LABEL(S) REQUIRED: Class 9

REPORTABLE QUANTITY: Not applicable.

FREIGHT CLASSIFICATION: 65 Petroleum Oil, n.o.i.b.n.

SPECIAL TRANSPORTATION NOTES: If shipped in containers of over 118.9 gallons capacity and above 100°C (212°F), regulated as an elevated temperature liquid, n.o.s. (at or above 100°C (212°F) and below its flash point), (petroleum oil). Mark: HOT. I.D. No. 3257

#### ENVIRONMENTAL/SAFETY REGULATIONS - SECTION IX

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: CALIFLUX GP®

Page 4 of 4

### SECTION 313 (TITLE III SUPERFUND AMENDMENT AND REAUTHORIZATION ACT):

This product does not contain any chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

- 19 (Հայաստանին) - 19 (Հայաստանի համարականի հայտարի հայտարի հայտարի հայտարի հայտարի հայտարի հայտարական հայտար - 19 (Հայաստանի հայտարական հայտարական հայտարական հայտարական հայտարական հայտարական հայտարական հայտարական հայտար

### COMMENTS - SECTION X

This product contains petroleum oils similar to ones categorized by the International Agency for Research on Cancer (IARC) as causing skin cancer in mice after prolonged and repeated contact. Any potential hazard can be minimized by using recommended protective equipment to avoid skin contact and by washing thoroughly after handling.

PREPARED BY: J. L. Davis. TITLE: Laboratory Director. ORIGINAL DATE: 07/16/97. REVISION DATE: 07/16/97.

SUPERSEDES:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.