



SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

A-151NT/STHL DR/181KG

Section 1. Product and company identification

Product name : A-151NT/STHL DR/181KG

Chemical name : Vinyltriethoxysilane

Manufacturer/Importer/ :

Distributor Information

Momentive Performance Materials - Sistersville

10851 Energy Highway FRIENDLY WV 26146

Contact person : 4information@momentive.com

Telephone : General information

+1-800-295-2392

Emergency telephone number

Supplier : CHEMTREC

1-800-424-9300

Section 2. Hazards identification

Classification of the substance or

mixture

GHS label elements

FLAMMABLE LIQUIDS - Category 3

Hazard pictograms

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapor.

Precautionary statements

General : Not applicable.

Prevention: Wear protective gloves.

Wear eye or face protection.

Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

Use explosion-proof electrical, ventilating, lighting and all material-

handling equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Response : IF ON SKIN (or hair):

Take off immediately all contaminated clothing.

Rinse skin with water or shower.

Storage : P403Store in a well-ventilated place.

P235Keep cool.

Disposal : P501Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Other hazards which do not result in classification

: Additional ethanol may be formed by reaction with moisture.

Section 3. Composition/information on ingredients

Substance/mixture : Substance

Chemical name : Vinyltriethoxysilane

CAS number/other identifiers

CAS number : 78-08-0 **EC number** : 201-081-7

Hazardous ingredients	% by weight	CAS
		number
Silane, ethenyltriethoxy-	98.5	78-08-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if

irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove

contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before

reuse.

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place

A-151NT/STHL DR/181KG Page:3/11

in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first aid personnel : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media Use dry chemical, CO2, water spray (fog) or foam.

Do not use water jet.

Specific hazards arising from the chemical

Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides silicon oxides

Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are

formed due to oxidative degradation.

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to

any waterway, sewer or drain.

Special protective equipment for fire-fighters

: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see section 8 of SDS). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled

A-151NT/STHL DR/181KG Page: 5/11

containers. Use appropriate containment to avoid environmental contamination.

Recommended Handling and storage Conditions

Do not store above the following temperature: $100 \, ^{\circ}\text{C}$ Ambient Conditions.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

A-151NT/STHL DR/181KG

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid Color : Light yellow

Odor : ester-like
Odor threshold : Not available
pH : Not available
Melting point : <0 °C (32.00 °F)

Boiling point : 160.5 °C (320.90 °F)

Flash point : 44 °C (111.20 °F) (Tag Closed Cup)

Burning time: Not availableBurning rate: Not available

Evaporation rate : <1

(n-Butyl acetate=1)

Flammability (solid, gas) : Not available

Lower and upper explosive : Lower: Not available (flammable) limits : Upper: Not available

Vapor pressure: Not availableVapor density: > 1 [Air = 1]

Relative density : 0.91

Density : 0.9050 g/cm3

Solubility : Not available **Solubility in water** : Reactive

Partition coefficient: n-

octanol/water

Not available

Auto-ignition temperature : Not available
Decomposition temperature : Not available
SADT : Not available

Viscosity : Dynamic: Not available
Kinematic: Not available

Other information

No additional information.

Section 10. Stability and reactivity

Reactivity : Stable under normal conditions.

Chemical stability : The product is stable.

A-151NT/STHL DR/181KG Page:7/11

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions

will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not

pressurize, cut, weld, braze, solder, drill, grind or expose containers

to heat or sources of ignition.

Incompatible materials: Reactive or incompatible with the following materials:

oxidizing materials

Reacts with water forming ethanol.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous

decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
Silane, ethenyltriethoxy-					
	LD50 Oral	Rat	23 mg/kg	-	

Conclusion/Summary : Not determined

Irritation/Corrosion

Conclusion/Summary

Skin:Not determinedeyes:Not determinedRespiratory:Not determined

Sensitization

Conclusion/Summary

Skin : Not determined Respiratory : Not determined

Mutagenicity

Conclusion/Summary : Not determined

Carcinogenicity

Conclusion/Summary : Not determined

Reproductive toxicity

Conclusion/Summary : Not determined

Teratogenicity

Conclusion/Summary : Not determined

Specific target organ toxicity (single exposure)

Not available

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Not available

Information on the likely routes of : Not available

exposure

Potential acute health effects

Eve contact No known significant effects or critical hazards. Inhalation No known significant effects or critical hazards. Skin contact No known significant effects or critical hazards. **Ingestion** No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data. Inhalation No specific data. : Skin contact No specific data. Ingestion No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Not available **Potential immediate effects** Not available Potential delayed effects

Long term exposure

Potential immediate effects Not available Potential delayed effects Not available

Potential chronic health effects

Conclusion/Summary Not determined

No known significant effects or critical hazards. General Carcinogenicity No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. **Teratogenicity** No known significant effects or critical hazards. **Developmental effects** No known significant effects or critical hazards. **Fertility effects** No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available

Section 12. Ecological information

Ecotoxicity

Conclusion/Summary : Not available

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
triethoxy(vinyl)silane		=		
Remarks:	Readily biodegrada	ble	_	

Conclusion/Summary : Not available

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. See Section 8 for information on appropriate personal protective equipment.

Section 14. Transport information

DOT SHIPPING NAME: Flammable liquids, n.o.s.(triethoxy(vinyl)silane)

DOT HAZARD CLASS: 3
DOT LABEL (S): 3
UN/NA NUMBER: UN1993
PACKING GROUP: III

IMDG SHIPPING NAME: Flammable liquids, n.o.s.(triethoxy(vinyl)silane)

CLASS: 3 IMDG-Labels: 3

UN NUMBER: UN1993
PACKING GROUP: III
EmS No.: F-E; S-E

IATA: Flammable liquids, n.o.s.(triethoxy(vinyl)silane)

CLASS: 3
ICAO-Labels: 3
UN NUMBER: UN

UN NUMBER: UN1993 PACKING GROUP: III

Special precautions for user : Transport within user's premises: always transport in closed

containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an

accident or spillage.'

15. Regulatory information

United States

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

required.

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed

SARA 311/312

Classification : Fire hazard

California Prop. 65: None required.

Canada

WHMIS (Canada) : Class B-3: Combustible liquid with a flash point between 37.8°C

(100°F) and 93.3°C (200°F).

Class D-2B: Material causing other toxic effects (Toxic).

International regulations

International lists : Australia inventory (AICS): All components are listed or exempted.

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted. **Canada inventory:** All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

United States inventory (TSCA 8b): All components are listed or exempted.

New Zealand Inventory (NZIoC): At least one component is not listed.

Taiwan inventory (CSNN): All components are listed or exempted.

Section 16. Other information

${\bf Hazardous\ Material\ Information\ System\ III\ (U.S.A.):}$

Health	1	
Flammability	2	
Physical hazards	1	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

Full text of abbreviated H

statements

Not applicable.

History

Date of printing: 06/26/2015Date of issue/Date of revision: 05/28/2015Date of previous issue: 00/00/0000

Version : 1.0

Prepared by: Product Safety StewardshipKey to abbreviations: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

References : Not available

Notice to reader

Unless otherwise specified in section 1, Momentive Products are intended for industrial application only. They are not intended for specific medical applications, neither for long-lasting (> 30 days) implantation into the human body, injected or directly ingested, nor for the manufacture of multiple usable contraceptives Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

®,*, and TM indicate trademarks owned by or licensed to Momentive.