

**NATROCHEM, INC.**

Post Office Box 1205  
Savannah, Georgia 31402-1205  
(912) 236-4464

**MATERIAL SAFETY  
DATA SHEET****STAN-MASK 21600 DLC®-A**

Date Revised: November 18, 1998

Page 1 of 4

**SECTION I - PRODUCT IDENTIFICATION**

TRADE NAME: Stan-mask 21600 DLC-A  
CHEMICAL NAME: Blended aromatic chemicals and natural products on silicon dioxide

HMIS RATING	
Health	1
Flammability	2
Reactivity	0

**SECTION II - COMPONENTS**

COMPONENT NAME	CAS#
Proprietary formulation	
Silicon Dioxide	7531-86-9

**SECTION III - PHYSICAL DATA**

Boiling Point: N/A	Specific Gravity: 1.02 (calculated)
Vapor Pressure (mm Hg): N/A	Percent Volatiles: N/DA
Vapor Density (Air = 1): N/A	Evaporation Rate: N/A
Solubility in Water: Insoluble	
Appearance and Odor: Off-white, free flowing powder with lemon odor.	

**SECTION IV - FIRE & EXPLOSION DATA**

FLASH POINT (Method Used): 125°F (CC)  
FLAMMABLE LIMITS: N/A  
AUTOIGNITION TEMPERATURE: N/A

EXTINGUISHING MEDIA: CO<sub>2</sub>, foam, and dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE &amp; EXPLOSION HAZARDS: None Known.

**SECTION V - HEALTH HAZARD DATA**

**CHRONIC HEALTH EFFECTS:** An epidemiological study was conducted which included 165 precipitated silica workers who had been exposed for an average of 18 years. No adverse effects were noted in complete medical examination (including chest roentgenograms) of these workers. Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposure. Laboratory studies have also been conducted in small animals via inhalation to levels of precipitated silica dust of up to 126 mg/m<sup>3</sup> for periods from six months to two years. Although precipitated silica was temporarily deposited in the animals lungs, most of the deposited material was cleared soon after the dust exposure ended. The results of all studies performed by, or known to, PPG indicate a very low order of pulmonary activity for synthetic precipitated silica.

MARKETED BY

**HARWICK STANDARD**  
**DISTRIBUTION CORPORATION**  
60 S. Seiberling Street • Akron, Ohio 44305

STAN-MASK 21600 DLC-A

NATROCHEM MSDS

PAGE 2 OF 4

---

**SECTION V - HEALTH HAZARD DATA (cont)**

---

**PRIMARY ROUTE OF ENTRY-** Inhalation, skin contact, ingestion and eye contact.

**CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN:** None

**NTP:** No

**IARC:** No

**OSHA:** No

**EFFECTS OF EXPOSURE-**

**EYES-** Mildly irritating. Excessive contact with powder can cause drying of mucous membranes of eyes due to absorption of moisture and oils.

**SKIN-** Mildly irritating.

**INHALATION-** Nuisance dust. Excessive contact with powder can cause drying of mucous membranes of nose and throat due to absorption of moisture and oils. This material can also cause nasal irritation and nosebleeds. Irritating to the respiratory tract.

**INGESTION-** Harmful if swallowed.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE-** Persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear respiratory protection.

---

**SECTION VI - EMERGENCY & FIRST AID PROCEDURES**

---

**EYE CONTACT:** Immediately rinse with clean water for 15 minutes. Retract eyelids often. If irritation persists, seek medical attention.

**SKIN CONTACT:** Immediately remove contaminated clothing. Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes. Seek medical attention if ill effect or irritation develops.

**INHALATION:** If overcome by exposure, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult a physician.

**INGESTION:** Dilute with 16 ounces of water. Consult a physician.

---

**SECTION VII - REACTIVITY DATA**

---

**STABILITY:** Stable.

**MATERIALS TO AVOID-** Avoid alteration of product properties before reuse. Calcining, which may result in crystalline formation or mixing with additives may alter toxicological properties.

**CONDITIONS TO AVOID-** Avoid high temperatures (> 800 C) treatment.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon when burned.

**HAZARDOUS POLYMERIZATION:** Will not occur.

---

STAN-MASK 21600 DLC-A

NATROCHEM MSDS

PAGE 3 OF 4

---

**SECTION VIII - SPILL OR LEAK PROCEDURES**

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** MINIMIZE SPILL AREA. Vacuum spill material and place in closed plastic bags for disposal.

**WASTE DISPOSAL METHOD:** In accordance with local, state, and federal regulations.

---

**SECTION IX - SPECIAL PROTECTION INFORMATION**

---

**RESPIRATORY PROTECTION:** Use a respirator such as 3M 9900 or equivalent for protection against pneumoconiosis producing dusts.

**VENTILATION:** Provide explosion proof ventilation as required to control airborne dust levels. The sum total of all ingredients may emit vapors during normal processing. All possible health effects are not known and individual sensitivities will vary. Effective exhaust ventilation should always be provided to draw dust, fumes and vapors away from workers to prevent routine inhalation. Ventilation should be adequate to maintain ambient workplace atmosphere below the limits listed in Section V.

**PROTECTIVE GLOVES:** Impervious gloves to protect against contact with product.

**EYE PROTECTION:** Safety goggles.

**OTHER PROTECTIVE EQUIPMENT:** Protective clothing, eye wash station, safety shower.

---

**SECTION X - SPECIAL PRECAUTIONS**

---

**HANDLING AND STORAGE:** Handling can create explosive dust clouds. Eliminate ignition sources, use explosive proof equipment. Conveying and processing equipment should be spark-proof, well bonded and grounded. Avoid dust accumulations.

**OTHER PRECAUTIONS:** Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Launder contaminated clothing before reuse.

---

**SECTION XI - REGULATORY INFORMATION**

---

**TOXIC SUBSTANCE CONTROL ACT (TSCA):**

The components of this product are contained on the Inventory of the Toxic Substance Control Act.

---

STAN-MASK 21600 DLC-A

NATROCHEM MSDS

PAGE 4 OF 4

**SECTION XI - REGULATORY INFORMATION (Cont.)****CHEMICAL INVENTORIES:****OSHA:**

The component(s) listed below is identified as a hazardous chemical under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

INGREDIENT	ACGIH (TLV)	OSHA (PEL)	UNITS
Silicon Dioxide	10	6	mg/m3

**SARA TITLE III INFORMATION:****SECTION 313 - TOXIC CHEMICALS:**

This product does contain the following toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act and 40 CFR 372.

CAS REGISTRY #	CHEMICAL NAME	PERCENT BY WEIGHT
None.		

**SECTION 311/312 - HAZARD CATEGORIES:**

The physical and health hazard categories for this product are:

Silicon Dioxide - Acute Hazard - 28%

**RCRA:**

This product is not a hazardous waste as listed in 40CFR 261.33. It does not exhibit any of the hazardous characteristics listed in 40CFR 261 Subpart C.

**TRANSPORTATION INFORMATION:**

DOT Shipping Name: Not DOT regulated

DOT Identification Number: N/A

**SECTION XII - OTHER INFORMATION**

Revision Note: New issue of MSDS.

Prepared by: James L. Pye, Jr.

Title: Safety Coordinator

N/A = Not applicable N/D = Not determined N/DA = No Data Available N/E = Not established

The information given in this MSDS was obtained from sources which we believe are reliable. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, Natrochem, Inc. makes no warranty express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon.