

NATROCHEM, INC.

Post Office Box 1205 Savannah, Georgia 31402-1205 (912) 236-4464

MATERIAL SAFETY DATA SHEET

Plasticizer SC-B DLC®-A

Date Revised: April 4, 2000 <u>Page</u> 1 of 4 SECTION 1 - PRODUCT IDENTIFICATION TRADE NAME: Plasticizer SC-B DLC-A **HMIS RATING** CHEMICAL NAME: Decanoic Acid, Mixed diesters with Octanoic Acid and HEALTH 1 **FLAMMABILITY** 1 Triethylone glycol on silicon dioxide REACTIVITY Ω SECTION II - COMPONENTS COMPONENT NAME CAS# PEL : TLV **AWT** Silicon Dioxide 7631-86-9 N/DA N/DA 6mg/m3 (05HA) 10mg/m3 (ACGIH) Decanoic Acid, Mixed Diester with 68583-52-8 N/E N/DA Octanoic Acid and Triethylene glycol SECTION III - PHYSICAL DATA Boiling Point: 300°C Specific Gravity: 1.13 (Calculated) Vapor Pressure (mm Hg); N/A Percent Volatiles: N.DA Vapor Density (Air = 1): N/A Evaporation Rate: <1 Solubility in Water: Insoluble Appearance and Odor: Off-white, free flowing powder with no odor. SECTION IV - FIRE & EXPLOSION DATA FLASH POINT (Method Used): 94°C (PMCC) FLAMMABLE LIMITS: N/DA AUTOIGNITION TEMPERATURE: N/DA EXTINGUISHING MEDIA: Dry chemical, CO2, foam, or water fog SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE & EXPLOSION HAZARDS: None Known.

SECTION V - HEALTH HAZARD DATA

CHRONIC HEALTH EFFECTS: An epidemiological study was conducted which included 165 precipitated silica workers who had been exposed for an average of 18 years. No adverse effects were noted in complete medical examination (including chest roentgenograms) of these workers. Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposure. Laboratory studies have also been conducted in small animals via inhalation to levels of precipitated silica dust of up to 126 mg/m3 for periods from six months to two years. Although precipitated silica was temporarily deposited in the animals lungs, most of the deposited material was cleared soon after the dust exposure ended. The results of all studies performed by, or known to, PPG indicate a very low order of pulmonary activity for synthetic precipitated silica.

MARKETED BY

HARWICK STANDARD DISTRIBUTION CORPORATION

60 S. Seiberling Street • Akron, Ohio 44305

Plasticizer SC-B DLC-A

NATROCHEM MSDS

PAGE 2 OF 4

SECTION V - HEALTH HAZARD DATA (cont)

PRIMARY ROUTE OF ENTRY- Inhalation

CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN: None

NTP: No

IARC: No

OSHA: No

TOXICITY:

LD50

- LC50

Triothylene Glycol

rat/oral >3.2g/kg

N/DA

Silicon Dioxido

acute oral > 5g/kg

Acute Inhalation: Nuisance dust

EFFECTS OF EXPOSURE-

EYES- Mildly irritating. Excessive contact with powder can cause drying of mucous membranes of eyes due to absorption of moisture and oils.

SKIN- Mildly irritating.

INHALATION- Nuisance dust. Excessive contact with powder can cause drying of mucous membranes of nose and throat due to absorption of moisture and oils. This material can also cause nasal irritation.

INGESTION- Not significantly toxic.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE- Persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear respiratory protection.

SECTION VI - EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: Immediately rinse with clean water for 15 minutes. Retract eyelids often. If irritation persists, seek medical attention.

SKIN CONTACT: Immediately remove contaminated clothing. Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes. Seek medical attention if ill offect or irritation devolops.

INHALATION: If overcome by exposure, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult a physician.

INGESTION: Consult a physician.

SECTION VII - REACTIVITY DATA

STABILITY: Stable.

MATERIALS TO AVOID- Avoid alteration of product properties before reuse. Calcining, which may result in crystalline formation or mixing with additives may alter toxicological properties. Strong exidizing agents, alkali, or caustic.

CONDITIONS TO AVOID- Avoid high temperatures (>800 C) treatment.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon when burned.

HAZARDOUS POLYMERIZATION: Will not occur.

INGREDIENT

Silicon Dioxide

Plasticizor SC-B DLC-A NATROCHEM MSDS <u> PAGE 3 OF 4</u> SECTION VIII - SPILL OR LEAK PROCEDURES STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: MINIMIZE SPILL AREA. Vacuum spill material and place in closed plastic bags for disposal. Prevent runoff from entering drains, sewers, or streams. WASTE DISPOSAL METHOD: In accordance with local, state, and federal regulations. SECTION IX - SPECIAL PROTECTION INFORMATION RESPIRATORY PROTECTION: Use a respirator such as 3M 9900 or equivalent for protection against pneumoconiosis producing dusts. VENTILATION: Provide explosion proof ventilation as required to control airborne dust levels. The sum total of all ingredients may omit vapors during normal processing. All possible health offects are not known and individual sensitivities will vary. Effective exhaust ventilation should always be provided to draw dust, fumes and vapors away from workers to prevent routine inhalation. Ventilation should be adequate to maintain ambient workplace atmosphere below the limits listed in Section V. PROTECTIVE GLOVES: Impervious gloves to protect against contact with product. EYE PROTECTION: Safety goggles. OTHER PROTECTIVE EQUIPMENT: Protective clothing, eyo wash station, safety shower. SECTION X - SPECIAL PRECAUTIONS HANDLING AND STORAGE: Handling can create explosive dust clouds. Eliminate ignition sources, use explosive proof equipment. Convoying and processing equipment should be spark-proof, well bonded and grounded. Avoid dust accumulations. OTHER PRECAUTIONS: Wash with soap and water before eating, drinking, smoking, or using tollet facilities. Launder contaminated clothing before rouse. SECTION XI - REGULATORY INFORMATION TOXIC SUBSTANCE CONTROL ACT (TSCA): The components of this product are contained on the inventory of the Toxic Substance Control Act. CHEMICAL INVENTORIES: OSHA: The component(s) listed below is identified as a hazardous chemical under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200). AMOUNT ACGIH. **OSHA**

(TLV)

10

28%

(PEL)

UNITS

mg/m3

Plasticizer SC-B DLC-A

NATROCHEM MSDS

PAGE 4 OF 4

SECTION XI - REGULATORY INFORMATION (Cont.)

SARA 313 TOXIC CHEMICALS:

This product contains the following toxic chemical(s) subject to the reporting requirements of Soction 313 of Titlo III of the Superfund Amendments and Reauthorization Act of 1986 and the Pollution Prevention Act of 1990.

CAS REGISTRY #

CHEMICAL NAME

PERCENT BY WEIGHT

None.

This information must be included in all MSDS's that are copied and distributed for this material.

SECTION 311/312 - HAZARD CATEGORIES:

The physical and health hazard categories for the hazardous components exceeding the de minimis amount subject to reporting under Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372

Name of Chemical

Hazard

Percent in Product

Silicon Dioxide

Acute

28%

ADDITIONAL RIGHT-TO-KNOW INFORMATION ON COMPONENTS: None Known.

TRANSPORTATION INFORMATION:

DOT Shipping Name: Not DOT Regulated.

DOT Identification Number:

SECTION XII - OTHER INFORMATION

Revision Note: New issue MSDS.
Prepared by: James L. Pye, Jr.
Title: Safety Coordinator.

N/A = Not applicable N/D = Not determined N/DA = No Data Available N/E = Not established

The information given in this MSDS was obtained from sources which we believe are reliable. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control. Natrochem, Inc. makes no warranty express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon.