

MATERIAL SAFETY DATA SHEET

AQUAMIX 131

Version Number 1.0 Revision Date 10/30/2002 Page 1 of 6 Print Date 12/15/2003

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY

Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number

or accident).

Product name Product code AQUAMIX 131 FO00002898

Chemical Name CAS-No.

Mixture Mixture

Product Use

Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Ziram	137-30-4	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product is a water based mixture with an ammonia odor. The mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. The product is not combustible, but it will burn if involved in a fire, releasing hydrocarbon products of combustion. Inhalation of the ammonia from this product may cause respiratory irritation, coughing, sore throat, and labored breathing.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Skin contact, Inhalation, Ingestion

Acute exposure

Inhalation

: Symptoms of breathing ammonia vapor concentrated from this product

may include laryngitis, tracheitis, pulmonary edema, dyspnea, bronchospasms, and chest pains or pneumonitis. Symptoms are

typically reversible.

Ingestion

May be harmful if swallowed.

Eyes

 Liquid, aerosol, or vapors of this product are irritating and may cause tearing, reddening, and swelling accompanied by a stinging sensation

and/or a feeling like that of fine dust in the eyes.

Skin

: Skin contact may cause redness, irritation, and burns.

1/6



MATERIAL SAFETY DATA SHEET

AQUAMIX 131

Version Number 1.0 Revision Date 10/30/2002

Page 2 of 6 Print Date 12/15/2003

Chronic exposure

: Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: None known

4. FIRST AID MEASURES

Inhalation Move to fresh air in case of accidental inhalation of vapors or fumes

from overheating or combustion. When symptoms persist or in all

cases of doubt seek medical advice.

Do not induce vomiting without medical advice. Never give anything Ingestion

by mouth to an unconscious person. Seek medical attention if

necessary.

Eyes Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point No data available.

Flammable Limits

Upper explosion limit No data available.

Lower explosion limit No data available. Autoignition temperature No data available.

Suitable extinguishing media carbon dioxide (CO2), water, foam, dry chemical.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water

courses.

Unusual Fire/Explosion

Hazards

Burning dry latex produces dense black smoke with the possibility of

toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure response personnel are properly protected (see section 8 for

respiratory or other protection guidelines.) Use caution as floors may

be slippery.

Environmental precautions The product should not be allowed to enter drains, water courses or

the soil.

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Sweep up and shovel into suitable



MATERIAL SAFETY DATA SHEET

AQUAMIX 131

Version Number 1.0 Revision Date 10/30/2002

Page 3 of 6 Print Date 12/15/2003

containers for disposal.

7. HANDLING AND STORAGE

Handling

Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may

be necessary before use.

Storage

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection

A respirator is normally not required for routine handling of product in areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. If using a cartridge respirator, an ammonia cartridge is required to filter out potential excess ammonia vapors.

Eye/Face Protection

Safety glasses with side-shields. Wear goggles or face shield during operations that present a splash potential.

Hand protection

Impervious gloves such as rubber or PVC

Skin and body protection

Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.

Additional Protective

Measures

Safety shoes

General Hygiene Considerations

Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and

safety practices.

Engineering measures

Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing

vapors.

Exposure limit(s)

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: Liquid

Evaporation rate

Slower than Butyl

Appearance

: Liquid

Specific Gravity

Not determined

Acetate



MATERIAL SAFETY DATA SHEET

AQUAMIX 131

Version Number 1.0 Revision Date 10/30/2002 Page 4 of 6

Print Date 12/15/2003

Color Odor Melting point/range

: NO PIGMENT : Slight ammonia : Not applicable : Not applicable

Bulk density Vapor pressure Vapor density pН

Not applicable. Not established Heavier than air. Not determined

Boiling Point: Water solubility

: Completely miscible

10. STABILITY AND REACTIVITY

Stability

Stable.

Hazardous Polymerization

Will not occur.

Conditions to avoid

Extremes of temperature and direct sunlight. Keep from freezing.

Incompatible Materials

Acids, metal salts, and solvents

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
137-30-4	Ziram	Systemic effects	Liver, Kidney, reproductive system.
		toxic	Refer to LC50 / LD50 Data on MSDS

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
137-30-4	Ziram	LC50	81 mg/m3	rat
		Oral LD50	267 mg/kg	rat
	*	Dermal LD50	> 2 gm/kg	rabbit

Additional Health Hazard Information:

Ziram 137-30-4 Highly toxic, irritant and a skin sensitizer. This material if ingested my cause an Antabuse response when alcohol is ingested. This Antabuse effect includes nausea, vomiting, abdominal cramps and/or flushing.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: No data available.



MATERIAL SAFETY DATA SHEET

AQUAMIX 131

Version Number 1.0 Revision Date 10/30/2002 Page 5 of 6 Print Date 12/15/2003

Environmental Toxicity

: No data available.

Bioaccumulation Potential

No data available.

Additional advice

No data available.

13. DISPOSAL CONSIDERATIONS

Product

Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging

Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification

Refer to specific regulation.

ICAO/IATA

Refer to specific regulation.

IMO / IMDG

Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status

: Classified as hazardous based on components.

TSCA Status

All components of this product are listed on the TSCA inventory or

are exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for
			_	Mixture/Product
Ziram	137-30-4	50.0000	001 lbs	2 LB

California Proposition

WARNING! This product contains a chemical known to the State of

65

California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

5/6



MATERIAL SAFETY DATA SHEET

AQUAMIX 131

Version Number 1.0 Revision Date 10/30/2002

Page 6 of 6 Print Date 12/15/2003

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ZINC COMPOUNDS	137-30-4	50.00

Canadian Regulations:

WHMIS Classification

: D1B

DSL

: Listed.

National Inventories:

Australia AICS

Not determined.

China IECS

Not determined.

Europe EINECS

Not determined.

Japan ENCS

Not determined.

Korea KECI

Not determined.

Philippines PICCS

Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.