MATERIAL SAFETY DATA SHEET



## MASTERMIX DPG 4474 SLAB BLUE

Version Number 1.7 Revision Date 09/30/2004

Page 1 of 7 Print Date 10/2/2004

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### **EXCEL POLYMERS LLC**

14330 Kinsman Road, Burton, OH 44021

Telephone : Product Stewardship (440) 834-4644

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : MASTERMIX DPG 4474 SLAB BLUE

Product code : AD00000629 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,3-Diphenylguanidine	102-06-7	60 - 100
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	1 - 5
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	1 - 5
Stearic acid	57-11-4	1 - 5

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Particulates, like other inert materials can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Particulates, like other inert materials can be mechanically irritating.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

MATERIAL SAFETY DATA SHEET



### MASTERMIX DPG 4474 SLAB BLUE

Version Number 1.7 Revision Date 09/30/2004

Page 2 of 7 Print Date 10/2/2004

Chronic exposure

: Refer to Section 11 for Toxicological Information.

Medical Conditions
Aggravated by Exposure:

: None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

**5. FIRE-FIGHTING MEASURES** 

Flash point : Not applicable

Flammable Limits

Upper explosion limit

Lower explosion limit

Autoignition temperature Suitable extinguishing media Not applicableNot applicable

Not applicable

: water spray, dry powder, foam, carbon dioxide (CO2)none.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section

13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

**MATERIAL SAFETY DATA SHEET** 



### MASTERMIX DPG 4474 SLAB BLUE

Version Number 1.7 Revision Date 09/30/2004

Page 3 of 7 Print Date 10/2/2004

Handling

: Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.

Storage

Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection

: No personal respiratory protective equipment normally required when

handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this

material.

**Eye/Face Protection** 

Safety glasses with side-shields.

Hand protection

Protective gloves.

Skin and body protection

Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures

Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

#### Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Petroleum distillates,	500 ppm	PEL:	Vapor.	OSHA Z1
hydrotreated heavy	2,000		1	
naphthenic	mg/m3		-	
Petroleum distillates,	500 ppm	PEL:	Vapor.	OSHA Z1
hydrotreated light	2,000		· ·	
naphthenic	mg/m3			
Stearic acid	10 mg/m3	Time Weighted Average (TWA):	Total dust. as stearates	ACGIH

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid Evaporation rate : Not applicable
Appearance : Pellets, slabs, sheets Specific Gravity: : Not determined
Color : NOT APPLICABLE Bulk density : Not established
Odor : Characteristic rubber odor Vapor pressure : Not applicable

MATERIAL SAFETY DATA SHEET



## MASTERMIX DPG 4474 SLAB BLUE

Version Number 1.7 Revision Date 09/30/2004

Page 4 of 7 Print Date 10/2/2004

Melting point/range

: Not determined

**Boiling Point:** 

: Not applicable

Vapour density pН

Not applicable Not applicable

Water solubility

: Insoluble

10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization

Will not occur.

Conditions to avoid

Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials

Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
102-06-7	1,3-Diphenylguanidine	Systemic effects	Respiratory system.
		toxic	Refer to LC50 / LD50 Data on MSDS
64742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	Irritant	Eyes, Skin.
64742-53-6	Petroleum distillates, hydrotreated light naphthenic	Irritant	Eyes, Skin.
57-11-4	Stearic acid	Irritant	Eyes, Skin.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
102-06-7	1,3-Diphenylguanidine	Oral LD50	323 mg/kg	rat
		Dermal LD50	> 794 mg/kg	rabbit
57-11-4	Stearic acid			
		Dermal LD50	> 5 gm/kg	rabbit

#### 12. ECOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET



### MASTERMIX DPG 4474 SLAB BLUE

Version Number 1.7 Revision Date 09/30/2004

Page 5 of 7 Print Date 10/2/2004

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the

polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the

polymer matrix.

Additional advice : Not applicable

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA (air) : Refer to specific regulation.

IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

65

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

65.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : This product does not contain a substance listed by California Prop

MATERIAL SAFETY DATA SHEET



## MASTERMIX DPG 4474 SLAB BLUE

Version Number 1.7 Revision Date 09/30/2004

Page 6 of 7 Print Date 10/2/2004

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)-	9016-45-9	0.97	183
.omegahydroxy-			

WHMIS Classification : D1B

WHMIS Ingredient Disclosure List

CAS-No.	
57-11-4	

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Listed

Philippines PICCS : Listed

### 16. OTHER INFORMATION

MATERIAL SAFETY DATA SHEET



# MASTERMIX DPG 4474 SLAB BLUE

Version Number 1.7 Revision Date 09/30/2004

Page 7 of 7 Print Date 10/2/2004

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.