

MATERIAL SAFETY DATA SHEET

POLYBOUND 424 CUREBLEND-80

Version Number 1.0 Revision Date 11/26/2002

Page 1 of 7 Print Date 2/3/2003

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

14330 Kinsman Road, Burton, OH 44021

NON-EMERGENCY

: Product Stewardship (440)-834-4644

TELEPHONE

number

Emergency telephone

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

or accident).

Product name

: POLYBOUND 424 CUREBLEND-80

Product code

: AD0000043410 : Mixture

Chemical Name CAS-No.

: Mixture

Product Use

Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|--|------------|----------|
| 2-Mercaptobenzothiazole | 149-30-4 | 5 - 10 |
| Di-2-benzothiazolyl disulfide | 120-78-5 | 5 - 10 |
| Silica, amorphous | 7631-86-9 | 1 - 5 |
| Petroleum distillates, hydrotreated light naphthenic | 64742-53-6 | 5 - 10 |
| Petroleum distillates, hydrotreated heavy naphthenic | 64742-52-5 | 10 - 30 |
| Tetramethyl thiuram disulfide (Thiram) | 137-26-8 | 10 - 30 |
| Zinc oxide | 1314-13-2 | 30 - 60 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation

: Resin particles, like other inert materials, can be mechanically

irritating.

Ingestion

: May be harmful if swallowed.

MARKETED BY
HARWICK STANDARD
DISTRIBUTION CORPORATION
60 S. Seiberling Street • Akron, Ohio 44305



MATERIAL SAFETY DATA SHEET

POLYBOUND 424 CUREBLEND-80

Version Number 1.0 Revision Date 11/26/2002

Page 2 of 7 Print Date 2/3/2003

Eyes

Resin particles, like other inert materials, are mechanically irritating to

eves.

Skin

: Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure

: Refer to Section 11 for Toxicological Information.

Medical Conditions
Aggravated by Exposure:

None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point

: Not applicable

Flammable Limits

Upper explosion limit

: Not applicable

Lower explosion limit Autoignition temperature

Not applicable Not relevant

Suitable extinguishing media

: Water spray, dry powder, foam, carbon dioxide (CO2).

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

None

:

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions

Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up

Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section



MATERIAL SAFETY DATA SHEET

POLYBOUND 424 CUREBLEND-80

Version Number 1.0 Revision Date 11/26/2002

Page 3 of 7 Print Date 2/3/2003

13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling

Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.

Storage

Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection

No personal respiratory protective equipment normally required when

handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this

material.

Eye/Face Protection

Safety glasses with side-shields.

Hand protection

Protective gloves.

Skin and body protection

Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene

Considerations

Handle in accordance with good industrial hygiene and safety

practice. Wash hands before breaks and at the end of workday.

Engineering measures

Heat only in areas with appropriate exhaust ventilation. Adequate

ventilation and/or appropriate respiratory protection may also be

necessary to minimize employee exposure to processing vapors.

Exposure limit(s)



MATERIAL SAFETY DATA SHEET

POLYBOUND 424 CUREBLEND-80

Version Number 1.0 Revision Date 11/26/2002

Page 4 of 7 Print Date 2/3/2003

| Components | Value | Exposure time | Exposure type | List: |
|------------------------|----------|-----------------------|------------------------|---------|
| Petroleum distillates, | 500 ppm | PEL: | Vapor. | OSHA Z1 |
| hydrotreated heavy | 2,000 | | | |
| naphthenic | mg/m3 | | | |
| Petroleum distillates, | 500 ppm | PEL: | Vapor. | OSHA Z1 |
| hydrotreated light | 2,000 | | | |
| naphthenic | mg/m3 | | | |
| Silica, amorphous | 20 mppcf | PEL: | Total dust. | OSHA |
| Silica, amorphous | 20 mppcf | PEL: | Total dust. | Z3 |
| Zinc oxide | 10 mg/m3 | Time Weighted Average | Total dust. as Zn | ACGIH |
| | | (TWA): | | |
| | 5 mg/m3 | PEL: | Respirable dust, as Zn | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. as Zn | OSHA Z1 |
| Tetramethyl thiuram | 1 mg/m3 | Time Weighted Average | Total dust. | ACGIH |
| disulfide (Thiram) | | (TWA): | | |
| Tetramethyl thiuram | 5 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| disulfide (Thiram) | | | | |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid Evaporation rate Not applicable. Appearance Not determined : Crumb Specific Gravity Color : NO PIGMENT Bulk density Not established Odor : Characteristic rubber odor Vapor pressure Not applicable Melting point/range : Not determined Vapor density Not applicable **Boiling Point:** Not applicable Not applicable pН

Water solubility : Insoluble

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

products (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:



MATERIAL SAFETY DATA SHEET

POLYBOUND 424 CUREBLEND-80

Version Number 1.0 Revision Date 11/26/2002

Page 5 of 7 Print Date 2/3/2003

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|--|------------------|--|
| 149-30-4 | 2-Mercaptobenzothiazole | toxic | Refer to LC50 / LD50 Data on MSDS |
| 120-78-5 | Di-2-benzothiazolyl disulfide | Systemic effects | reproductive system. |
| 7631-86-9 | Silica, amorphous | Irritant | Eyes, Respiratory system. |
| 64742-53-6 | Petroleum distillates, hydrotreated light naphthenic | Irritant | Eyes, Skin. |
| 64742-52-5 | Petroleum distillates, hydrotreated heavy naphthenic | Irritant | Eyes, Skin. |
| 137-26-8 | Tetramethyl thiuram disulfide (Thiram) | Irritant | Eyes, Skin, Respiratory system. |
| | | sensitizer | Eyes, Skin, Respiratory system. |
| | | Systemic effects | Liver, Kidney, central nervous system. |
| | | toxic | Refer to LC50 / LD50 Data on MSDS |
| 1314-13-2 | Zinc oxide | Systemic effects | Respiratory system. |

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|-------------------------|-------------|---------------|---------|
| 149-30-4 | 2-Mercaptobenzothiazole | LC50 | > 1270 mg/m3 | rat |
| | | Oral LD50 | 100 mg/kg | rat |
| <u> </u> | | Dermal LD50 | > 7,940 mg/kg | rabbit |
| 120-78-5 | Di-2-benzothiazolyl | Oral LD50 | > 12 gm/kg | rat |
| | disulfide | Dermal LD50 | > 7,940 mg/kg | rabbit |
| 137-26-8 | Tetramethyl thiuram | LC50 | 500 mg/m3 | rat |
| | disulfide (Thiram) | Oral LD50 | 210 mg/kg | rabbit |
| 1314-13-2 | Zinc oxide | LC50 | 2500 mg/m3 | mouse |
| | | Oral LD50 | 7,950 mg/kg | mouse |

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

Chemicals are not readily available as they are bound within the

matrix of the polymer.

Bioaccumulation Potential

: Chemicals are not readily available as they are bound within the

matrix of the polymer.

Additional advice

: Not applicable

13. DISPOSAL CONSIDERATIONS



MATERIAL SAFETY DATA SHEET

POLYBOUND 424 CUREBLEND-80

Version Number 1.0 Revision Date 11/26/2002

Page 6 of 7 Print Date 2/3/2003

Product : Where possible, recycling is preferred to disposal or incineration.

The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with

applicable federal, state/provincial and local regulations.

Contaminated packaging Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.

IMO / IMDG : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

65

OSHA Status : Classified as hazardous based on components.

TSCA Status : On TSCA List

US. EPA CERCLA Hazardous Substances (40 CFR 302)

| Chemical Name | CAS-No. | % in Product | RQ for component | RQ for Mixture/Product |
|--|----------|--------------|------------------|---------------------------|
| Tetramethyl thiuram disulfide (Thiram) | 137-26-8 | 10.5633 | 010 lbs | 95 LB |

California Proposition : This product

This product does not contain a substance listed by California Prop

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name | CAS-No. | Weight % |
|-------------------------|-----------|----------|
| 2-MERCAPTOBENZOTHIAZOLE | 149-30-4 | 08.80 |
| (MBT) | | |
| ZINC COMPOUNDS | 1314-13-2 | 35.55 |



MATERIAL SAFETY DATA SHEET

POLYBOUND 424 CUREBLEND-80

Version Number 1.0 Revision Date 11/26/2002 Page 7 of 7 Print Date 2/3/2003

| Chemical Name | CAS-No. | Weight % |
|---------------|----------|----------|
| THIRAM | 137-26-8 | 10.56 |

Canadian Regulations:

WHMIS Classification

D1B

WHMIS Ingredient Disclosure List

| CAS-No. |
|-----------|
| 7631-86-9 |
| 1314-13-2 |
| 120-78-5 |
| 137-26-8 |

DSL

Listed.

National Inventories:

Australia AICS

: Listed.

China IECS

Listed.

Europe EINECS

Listed.

Japan ENCS

Not determined.

Korea KECI

Listed.

Philippines PICCS

: Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.