MATERIAL SAFETY DATA SHEET

Version Number 1.2 Revision Date 04/09/2004 Page 1 of 6

Print Date 9/17/2004

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone

Product Stewardship (770) 590-3500 x.3563

Emergency telephone

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number

or accident).

Product name

: STAN-TONE HCC-12205 BLACK

Product code

FO00008451PA

Chemical Name

: Mixture : Mixture

CAS-No. Product Use

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation

: Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion

: May be harmful if swallowed.

Eyes

: May cause eye/skin irritation.

Skin

: Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure

: Refer to Section 11 for Toxicological Information.

Medical Conditions

: None known.

Aggravated by Exposure:

MARKETED BY

HARWICK STANDARD DISTRIBUTION CORPORATION

60 S. Seiberling Street • Akron, Ohio 44305



MATERIAL SAFETY DATA SHEET

Version Number 1.2 Revision Date 04/09/2004

Page 2 of 6 Print Date 9/17/2004

4. FIRST AID MEASURES

Inhalation Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Do not induce vomiting without medical advice. Seek medical Ingestion

attention if necessary.

Eyes Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Wash off with soap and plenty of water. If skin irritation persists Skin

seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point No data available

Flammable Limits

Upper explosion limit : No data available Lower explosion limit No data available

Autoignition temperature Not applicable

Carbon dioxide blanket, water spray, dry powder, foamnone. Suitable extinguishing media

Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive

pressure mode should be worn to prevent inhalation of airborne Procedures

contaminants.

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Unusual Fire/Explosion

Hazards (NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

: Wear appropriate personal protection during cleanup, such as Personal precautions

impervious gloves, boots and coveralls.

The product should not be allowed to enter drains, water courses or Environmental precautions

the soil. Should not be released into the environment.

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Package all material in

appropriate container for disposal. Refer to Section 13 of this MSDS

for proper disposal methods.

7. HANDLING AND STORAGE

: Heat only in areas with appropriate exhaust ventilation. Prolonged Handling

heating may result in product degradation.



MATERIAL SAFETY DATA SHEET

Version Number 1.2 Revision Date 04/09/2004 Page 3 of 6

Print Date 9/17/2004

Storage

Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection

: Under normal handling conditions a respirator may not be required.

Eye/Face Protection

: Safety glasses with side-shields.

Hand protection

: Protective gloves.

Skin and body protection

: Long sleeved clothing.

Additional Protective

Measures

: Safety shoes.

General Hygiene

Considerations

: Handle in accordance with good industrial hygiene and safety

practice. Wash hands before breaks and at the end of workday.

Engineering measures

: Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust, as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust, as carbon black	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: liquid

Evaporation rate

: Not established

Арреатапсе

: liquid, Viscous liquid

Specific Gravity:

: Not determined

Color

dispersion

: Not applicable

BLACK

Bulk density Vapor pressure

: Not determined

Odor

: Very faint : Not applicable

Vapour density

: Heavier than air.

Melting point/range Boiling Point:

: Not applicable

pН

: Not determined

Water solubility

: Immiscible

10. STABILITY AND REACTIVITY

Stability

Stable.

Hazardous Polymerization

Will not occur.

Conditions to avoid

: Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

3/8



MATERIAL SAFETY DATA SHEET

Version Number 1.2 Revision Date 04/09/2004

Page 4 of 6

Print Date 9/17/2004

Incompatible Materials

: Incompatible with strong acids and oxidizing agents.

Hazardous decomposition products

•

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ	
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.	

LC50/LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

Environmental toxicity has not been established for this mixture as a

whole.

Bioaccumulation Potential

: No data available

Additional advice

: No data available

13. DISPOSAL CONSIDERATIONS

C/B

PAGE

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

Version Number 1.2 Revision Date 04/09/2004 Page 5 of 6 Print Date 9/17/2004

Product

Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging

: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification

: Refer to specific regulation.

ICAO/IATA (air)

: Refer to specific regulation.

IMO / IMDG (maritime)

: Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status

: Classified as hazardous based on components.

TSCA Status

All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition

This product does not contain a substance listed by California Prop

5

65

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable



MATERIAL SAFETY DATA SHEET

Version Number 1.2 Revision Date 04/09/2004

Page 6 of 6 Print Date 9/17/2004

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No. 1333-86-4

DSL

All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS

Listed

China IECS

Listed

Europe EINECS

Listed

Japan ENCS

: Not determined

Korea KECI

Listed

Philippines PICCS

Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.