

### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-12150 ORANGE

Version Number 1.0 Revision Date 10/29/2002 Page 1 of 7 Print Date 7/23/2003

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY

Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone

\_

telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Product name

number

: STAN-TONE HCC-12150 ORANGE

Product code

: FO00008423PA

Chemical Name

: Mixture

CAS-No.

: Mixture

Product Use

: Industrial Applications

# 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	1 - 5
Molybdate orange (Lead chromate pigment)	12656-85-8	30 - 60

### 3. HAZARDS IDENTIFICATION

# **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation

: Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion

: May be harmful if swallowed.

Eyes

: May cause eye/skin irritation.

Skin

: Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure

: Refer to Section 11 for Toxicological Information.

MARKETED BY
HARWICK STANDARD
DISTRIBUTION CORPORATION
60 S. Seiberling Street • Akron, Ohio 44305



### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-12150 ORANGE

Version Number 1.0 Revision Date 10/29/2002

Page 2 of 7 Print Date 7/23/2003

**Medical Conditions** 

: None known.

Aggravated by Exposure:

### 4. FIRST AID MEASURES

Inhalation

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion

Do not induce vomiting without medical advice. Seek medical attention if necessary.

Eyes

Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin

Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

### 5. FIRE-FIGHTING MEASURES

Flash point

No data available.

Flammable Limits

Upper explosion limit Lower explosion limit No data available. No data available. Not applicable.

Autoignition temperature Suitable extinguishing media

Carbon dioxide blanket, dry powder, foam, Water spray.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

None

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions

Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

# 7. HANDLING AND STORAGE

Handling

: Heat only in areas with appropriate exhaust ventilation. Prolonged



### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCG-12150 ORANGE

Version Number 1.0 Revision Date 10/29/2002

Page 3 of 7 Print Date 7/23/2003

heating may result in product degradation.

Storage

: Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection

: Under normal handling conditions a respirator may not be required.

Eye/Face Protection

: Safety glasses with side-shields.

Hand protection

: Protective gloves.

Skin and body protection

Long sleeved clothing.

Additional Protective

: Safety shoes.

Measures

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures

Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

# Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	Dust and fume. as Fe	ACGIH
Molybdate orange (Lead chromate pigment)	1 mg/m3	PEL:	as Cr	OSHA Z1
Molybdate orange (Lead chromate pigment)	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	OSHA
	0.10 mg/m3	Ceiling Limit Value:	as CrO3	OSHA Z2
Molybdate orange (Lead chromate pigment)	0.01 mg/m3	Time Weighted Average (TWA):	as Cr(VI)	ACGIH
Molybdate orange (Lead chromate pigment)	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	ACGIH

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: Liquid

Evaporation rate

: Not established

Appearance

: Liquid, Viscous liquid

Specific Gravity

: Not determined

dispersion



### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-12150 ORANGE

Version Number 1.0 Revision Date 10/29/2002

Page 4 of 7 Print Date 7/23/2003

Color Odor Melting point/range Boiling Point: Water solubility

: ORANGE: Very faint: Not applicable: Not applicable

Bulk density Vapor pressure Vapor density pH

Not applicable.Not determinedHeavier than air.Not determined

10. STABILITY AND REACTIVITY

Stability

: Stable.

: Immiscible

Hazardous Polymerization

: Will not occur.

Conditions to avoid

: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

Incompatible Materials

Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
12656-85-8	Molybdate orange (Lead chromate pigment)	Irritant	Eyes, Skin.
		Systemic effects	central nervous system, reproductive system.

## Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
12656-85-8	Molybdate orange (Lead	no	no	1
	chromate pigment)			

## IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

### NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.



# MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-12150 ORANGE

Version Number 1.0 Revision Date 10/29/2002

Page 5 of 7 Print Date 7/23/2003

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Molybdate orange (Lead chromate pigment) 12656-85-8 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

# 12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

**Environmental Toxicity** 

Environmental toxicity has not been established for this mixture as a

whole.

Bioaccumulation Potential

: No data available.

Additional advice

: No data available.

## 13. DISPOSAL CONSIDERATIONS

Product

: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging

: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

### 14. TRANSPORT INFORMATION

U.S. DOT Classification

: Refer to specific regulation.

ICAO/IATA

: Refer to specific regulation.

IMO / IMDG

: Refer to specific regulation.

# 15. REGULATORY INFORMATION

US Regulations:

**OSHA Status** 

: Classified as hazardous based on components.

TSCA Status

All components of this product are listed on the TSCA inventory or

are exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)



### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-12150 ORANGE

Version Number 1.0 Revision Date 10/29/2002

Page 6 of 7 Print Date 7/23/2003

Not applicable

California Proposition

65

WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a

chemical known to the State of California to cause birth defects or

other reproductive harm.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name CAS-No. Weight %

Canadian Regulations:

WHMIS Classification

: D2B

WHMIS Ingredient Disclosure List

CAS-No.	
1309-37-1	
12656-85-8	

DSL

: Listed.

National Inventories:

Australia AICS

: Listed.

China IECS

: Listed.

**Europe EINECS** 

: Listed.

Japan ENCS

: Not determined.

Korea KECI

: Listed.

Philippines PICCS

: Not determined.

### 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



MATERIAL SAFETY DATA SHEET

8	G.	×		ж.	233	100	200	10	ж.	335	M.	E		77	~~~	200	4.40		200		22		30000	œ.	- 100	~8		20	200	
S		33	7 89	# A	38	1.7	77000	# #	8.00	2 .	ч.	9 mmg	× ***	8 4	****	ana a	2000	- 18 <i>00</i>	20	88 T	98	200	480	8 2	oy.	á %	2.0	30	2337.3	3000
×	300	2.5	88	æ	8.	& `	Such	4 83	100	2 3	•	B0000	8F 2009	終る	W 2	233	380	887 -	4838	group.	A 8	5536	S27	ã ta	W.:	28	18.	83	Se 3	2000

Version Number 1.0 Revision Date 10/29/2002 Page 7 of 7 Print Date 7/23/2003