

LUPEROX® DHBP**1. PRODUCT AND COMPANY IDENTIFICATION****Company**

Arkema Inc.
900 First Avenue
King of Prussia, Pennsylvania 19406

Functional Additives

Customer Service Telephone Number: (800) 331-7654
(Monday through Friday, 8:00 AM to 5:00 PM EST)

Emergency Information

Transportation: CHEMTREC: (800) 424-9300
(24 hrs., 7 days a week)
Medical: Rocky Mountain Poison Center: (866) 767-5089
(24 hrs., 7 days a week)

Product Information

Product name: LUPEROX® DHBP
Synonyms: Not available
Molecular formula: C16 H34 O4
Chemical family: Organic peroxide - dialkyl peroxides
Product use: initiator/catalyst

2. HAZARDS IDENTIFICATION**Emergency Overview**

Color: Colourless to yellow.
Physical state: liquid
Odor: ether-like

***Classification of the substance or mixture:**

Flammable liquid., Category 4, H227
Organic peroxides, Type C, H242
Skin irritation, Category 2, H315
Eye irritation, Category 2A, H319

*For the full text of the H-Statements mentioned in this Section, see Section 16.

LUPEROX® DHBP**GHS-Labeling**

Hazard pictograms:



Signal word:

Danger**Hazard statements:**

- H227 : Combustible liquid.
- H242 : Heating may cause a fire.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.

Supplemental Hazard Statements:

- Organic peroxide.
- Hazardous decomposition may occur.

Precautionary statements:**Prevention:**

- P210 : Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P220 : Keep/Store away from clothing/ combustible materials.
- P234 : Keep only in original container.
- P264 : Wash skin thoroughly after handling.
- P280 : Wear protective gloves/ eye protection/ face protection.

Response:

- P302 + P352 : IF ON SKIN: Wash with plenty of soap and water.
- P305 + P351 + P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P332 + P313 : If skin irritation occurs: Get medical advice/ attention.
- P337 + P313 : If eye irritation persists: Get medical advice/ attention.
- P362 : Take off contaminated clothing and wash before reuse.
- P370 + P378 : In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

- P410 : Protect from sunlight.
- P411 + P235 : Maximum storage temperature is specified on label and in section 7 of SDS. Keep cool.
- P420 : Store away from other materials.

Disposal:

- P501 : Dispose of contents/ container to an approved waste disposal plant.

Supplemental information:

Product code: 797000

Version 2.3

Issued on: 08/04/2017

Page: 2 / 14

LUPEROX® DHBP

Potential Health Effects:

If swallowed may cause irritation of the digestive tract.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis[(1,1-dimethylethyl)	78-63-7	>= 92 - <= 98 %	H227, H242, H315
1,2-Dioxane, 3,3,6,6-tetramethyl-	22431-89-6	>= 2 - < 6 %	H242, H226, H335, H319, H315
Hydroperoxide, 4-[(1,1-dimethylethyl)dioxy]-1,1,4-trimethylpentyl	23661-84-9	>= 1 - < 5 %	H314, H318

**For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1. Description of necessary first-aid measures:

Inhalation:

If inhaled, remove victim to fresh air.

Skin:

In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

LUPEROX® DHBP**4.2. Most important symptoms/effects, acute and delayed:**

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information) and Section 11 (Toxicology Information) of this SDS.

4.3. Indication of immediate medical attention and special treatment needed, if necessary:

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

5. FIREFIGHTING MEASURES**Extinguishing media (suitable):**

Water spray, Carbon dioxide (CO₂), Foam, Dry chemical

Extinguishing media (unsuitable):

Water may be ineffective., Do not use a solid water stream as it may scatter and spread fire.

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Fight fire with large amounts of water from a safe distance.

Cool closed containers exposed to fire with water spray.

Closed containers of this material may explode when subjected to heat from surrounding fire.

After a fire, wait until the material has cooled to room temperature before initiating clean-up activities.

Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

Contact with materials to avoid or exposure to temperatures exceeding the SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may autoignite.

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

LUPEROX® DHBP**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:**

Prevent further leakage or spillage if you can do so without risk. Evacuate area of all unnecessary personnel. Ventilate the area. Eliminate all ignition sources. Avoid generation of vapors. Contain and collect spillage with non-combustible absorbent material such as sodium bicarbonate, sodium carbonate, calcium carbonate, clean sand or non-acidic clay and then wet down (dampen) the mixture with water. DO NOT USE peat moss. Sweep or scoop up using non-sparking tools and place into suitable properly labeled containers for prompt disposal. The sweepings should be wetted down further with water. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8.

7. HANDLING AND STORAGE**Handling****General information on handling:**

Contact with materials to avoid or exposure to temperatures exceeding the SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may autoignite.

Keep away from heat, sparks and flames.

Do not breathe vapor or mist.

Avoid contact with skin, eyes and clothing.

No smoking.

Use only with adequate ventilation.

Prevent product contamination.

Wash thoroughly after handling.

Keep container tightly closed and away from combustible materials.

Keep only in the original container.

Check that all equipment is properly grounded and installed to satisfy electrical classification requirements.

RESIDUAL VAPORS MAY EXPLODE ON IGNITION.

DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.

Do not reuse container as it may retain hazardous product residue.

Emptied container retains vapor and product residue.

Observe all labeled safeguards until container is cleaned, reconditioned or destroyed.

Storage**General information on storage conditions:**

Keep container closed when not in use. Outside or detached storage is preferred. Store in well ventilated area away from heat and sources of ignition such as flame, sparks and static electricity. Store in upright position only. Store in closed containers, in a secure area to prevent container damage and subsequent spillage. Ensure that all storage and handling equipment is properly grounded and installed to satisfy electrical classification requirements. Store out of direct sunlight in a cool well-ventilated place. Store in original container. Store away from combustibles and materials to avoid. Refer also to National Fire Protection Association (NFPA) Code 400, Hazardous Materials Code. Static electricity may accumulate when transferring material. All metal and groundable storage containers, including but not limited to drums, cylinders, Returnable Intermodal Bulk Containers (RIBCs) and Class C Flexible Intermodal Bulk Containers (FIBCs) must be bonded and grounded during filling and emptying operations. Observe all federal,

LUPEROX® DHBP

state and local regulations and National Fire Protection Association (NFPA) Codes which pertain to the specific local conditions of storage and use, including OSHA 29 CFR 1910.106 and NFPA 30, 70, 77, and 497. May form explosive peroxide on standing for a prolonged period in air.

Storage stability – Remarks:

Follow the recommended storage temperatures provided in this Section in order to maintain stability and oxygen content.

Storage incompatibility – General:

Store away from excessive heat, sources of ignition, and reactive materials.

Strong acids

Strong oxidizing agents

Reducing agents

Accelerators

Friedel - Crafts reaction catalyst

Brass

Copper

Iron

For all Organic Peroxides, compatible materials of contact are stainless steel 304 or 316 (preferred), high-density polyethylene (HDPE), polytetrafluoroethylene or glass linings.

Temperature tolerance – Do not store below:

50 °F (10 °C)

Temperature tolerance – Do not store above:

100 °F (38 °C)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Airborne Exposure Guidelines:****Engineering controls:**

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Consult ACGIH ventilation manual or NFPA Standard 91 for design of exhaust systems.

Respiratory protection:

Do not breathe vapor or mist. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. Full facepiece equipment is recommended and, if used, replaces need for face shield and/or chemical goggles. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

LUPEROX® DHBP

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Wear face shield and chemical resistant clothing such as a rubber apron when splashing may occur. Rinse immediately if skin is contaminated. Remove contaminated clothing immediately and wash before reuse. Clean protective equipment before reuse. Provide a safety shower at any location where skin contact can occur. Wash thoroughly after handling.

Eye protection:

Where there is potential for eye contact, wear a face shield, chemical goggles, and have eye flushing equipment immediately available.

9. PHYSICAL AND CHEMICAL PROPERTIES
--

Color:	Colourless to yellow.
Physical state:	liquid
Odor:	ether-like
Odor threshold:	No data available
Flash point	176 °F (80 °C)
Lower flammable limit (LFL):	No data available
Upper flammable limit (UFL):	No data available
pH:	No data available
Density:	0.87 g/cm ³ (68 °F (20 °C))
Specific Gravity (Relative density):	0.87 (68 °F (20 °C))
Vapor pressure:	6 mmHg (68 °F (20 °C))
Boiling point/boiling range:	Decomposes before boiling. Rate of decomposition increases with rising temperature.
Melting point/range:	46 °F (8 °C)
Freezing point:	46 °F (8 °C)sub-cools
Evaporation rate:	No data available
Solubility in water:	immiscible
Refractive index:	1.42 68 °F (20 °C)
Viscosity, dynamic:	No data available

LUPEROX® DHBP

Oil/water partition coefficient:	No data available.
Self-Accelerating Decomposition Temperature (SADT):	174 - 180 °F (79 - 82 °C) (Method: Rapid heat test)
Thermal decomposition:	No data available
Active oxygen content:	10.36 - 10.80 %
Flammability:	See GHS Classification in Section 2

10. STABILITY AND REACTIVITY**Stability:**

See HANDLING AND STORAGE section of this SDS for specified conditions. This material is chemically unstable and should only be handled under specified conditions.

Hazardous reactions:

Hazardous polymerization does not occur.

Materials to avoid:

Strong acids
Strong oxidizing agents
Reducing agents
Accelerators
Friedel - Crafts reaction catalyst
Brass
Copper
Iron

For all Organic Peroxides, compatible materials of contact are stainless steel 304 or 316 (preferred), high-density polyethylene (HDPE), polytetrafluoroethylene or glass linings.

Conditions / hazards to avoid:

See HANDLING AND STORAGE section of this SDS for specified conditions. See Hazardous Decomposition Products below. SADT - Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction. This reaction will generate flammable vapors which may autoignite. The length of time to generate a decomposition reaction, after the SADT has been reached or exceeded, is dependent upon how much the SADT has been exceeded and the length of time needed for the reaction exotherm (heat spike from increasing decomposition rate) to initiate a rapid decomposition reaction. Typically, SADT is inversely proportional to package size. Larger packages will have a lower SADT due to smaller ratio to heat transfer area to volume of product.

Hazardous decomposition products:

Temperatures at or above SADT can result in the release of hazardous decomposition products which are flammable and may autoignite.

Thermal decomposition giving flammable and toxic products :

Carbon oxides
Hazardous organic compounds

11. TOXICOLOGICAL INFORMATION

LUPEROX® DHBP

Data on this material and/or a similar material are summarized below.

Data for Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis(1,1-dimethylethyl) (78-63-7)**Acute toxicity****Oral:**

May be harmful if swallowed. (rat) LD₀ > 2,000 mg/kg.

Dermal:

May be harmful in contact with skin. (rabbit) LD₅₀ = 4,100 mg/kg.

Skin Irritation:

Causes skin irritation. (rabbit) Irritation Index: 2.3/8. (4 h)

Eye Irritation:

Causes mild eye irritation. (rabbit) Irritation Index: 1/110.

Skin Sensitization:

Not a sensitizer. Buehler Test. (guinea pig) No skin allergy was observed

Repeated dose toxicity

Repeated oral administration to rat / affected organ(s): liver, kidney / signs: changes in organ weights, changes in organ structure or function, hyaline droplet nephropathy

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in a laboratory test using: mice

Developmental toxicity

Exposure during pregnancy. oral (rat) / No birth defects were observed.

Data for 1,2-Dioxane, 3,3,6,6-tetramethyl- (22431-89-6)**Acute toxicity****Specific target organ toxicity - single exposure:**

May cause respiratory irritation.

Skin Irritation:

Causes skin irritation. (estimate based on composition)

Eye Irritation:

Causes serious eye irritation. (estimate based on composition)

Other information

The information presented is from representative materials in this chemical class. The results may vary

LUPEROX® DHBP

depending on the test substance.

Data for Hydroperoxide, 4-[(1,1-dimethylethyl)dioxy]-1,1,4-trimethylpentyl (23661-84-9)

Acute toxicity

Skin Irritation:

Causes severe skin burns. (rabbit) (estimate based on composition)

Eye Irritation:

Causes serious eye damage. (rabbit) (estimate based on composition)

12. ECOLOGICAL INFORMATION

Chemical Fate and Pathway

Data on this material and/or a similar material are summarized below.

Data for Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis[(1,1-dimethylethyl) (78-63-7)

Stability in water:

Half-life 2.7 h (@pH 4)

Half-life 2.7 h (@pH 7)

Half-life 2.8 h (@pH 9)

Biodegradation:

Not readily biodegradable. (60 d) biodegradation 0 %

Ecotoxicology

Data on this material and/or a similar material are summarized below.

Data for Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis[(1,1-dimethylethyl) (78-63-7)

Aquatic toxicity data:

No effect up to the limit of solubility. *Oryzias latipes* (Orange-red killifish) 96 h LC50 = 4.5 mg/l (nominal concentrations reported)

Algae:

No effect up to the limit of solubility. *Pseudokirchneriella subcapitata* 72 h EC50 > 0.236 mg/l (nominal concentrations reported)

Microorganisms:

No effect up to the limit of solubility. Activated sludge 3 h NOEC (Respiration inhibition) > 1,000 mg/l (nominal concentrations reported)

Chronic toxicity to aquatic invertebrates:

No effect up to the limit of solubility. semi-static test / *Daphnia magna* (Water flea) 21 d LOEC > 0.0065 mg/l

Chronic toxicity to aquatic plants:

No effect up to the limit of solubility. static test / *Pseudokirchneriella subcapitata* 72 h NOEC > 0.236 mg/l

LUPEROX® DHBP

13. DISPOSAL CONSIDERATIONS

Waste disposal:

Dilution followed by incineration is the preferred method. Dilution ratio of 10:1 in a clean, compatible, combustible solvent (i.e., Fuel Oil #2, mineral oil) will reduce reactivity hazard during incineration and transportation. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations. (concentrated solutions, then, diluted solutions).

14. TRANSPORT INFORMATION

US Department of Transportation (DOT)

UN Number : 3103
Proper shipping name : Organic peroxide type C, liquid
Technical name : (2,5-Dimethyl-2,5-di(tert-butylperoxy) hexane, > 90-100%)
Class : 5.2
Marine pollutant : no

International Maritime Dangerous Goods Code (IMDG)

UN Number : 3103
Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID
Technical name : (2,5-DIMETHYL-2,5-DI(TERT-BUTYLPEROXY) HEXANE, > 90-100%)
Class : 5.2
Marine pollutant : no
Flash point : 176 °F (80 °C)

15. REGULATORY INFORMATION

Chemical Inventory Status

US. Toxic Substances Control Act	TSCA	The components of this product are all on the TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to

LUPEROX® DHBP

Philippines Inventory of Chemicals and Chemical Substances (PICCS) PICCS (PH) Conforms to

Australia Inventory of Chemical Substances (AICS) AICS Conforms to

United States – Federal Regulations

SARA Title III – Section 302 Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

SARA Title III - Section 311/312 Hazard Categories:

Fire Hazard, Reactivity Hazard, Acute Health Hazard

SARA Title III – Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

<u>Chemical name</u>	<u>CAS-No.</u>	<u>Reportable quantity</u>
2-Propanol, 2-methyl-	75-65-0	100 lbs
Peroxide, bis(1,1-dimethylethyl)	110-05-4	100 lbs

United States – State Regulations

New Jersey Right to Know

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right to Know

<u>Chemical name</u>	<u>CAS-No.</u>
Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis[(1,1-dimethylethyl)	78-63-7
1,2-Dioxane, 3,3,6,6-tetramethyl-	22431-89-6
2-Propanol, 2-methyl-	75-65-0

Pennsylvania Right to Know – Environmentally Hazardous Substance(s)

<u>Chemical name</u>	<u>CAS-No.</u>
----------------------	----------------

LUPEROX® DHBP

2-Propanol, 2-methyl-

75-65-0

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

16. OTHER INFORMATION**Full text of H-Statements referred to under sections 2 and 3.**

H226 Flammable liquid and vapour.
H227 Combustible liquid.
H242 Heating may cause a fire.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Miscellaneous:

Other information: Refer to National Fire Protection Association (NFPA) Codes 30, 70, 77, and 497 and OSHA 29 CFR 1910.106, for safe handling.

Latest Revision(s):

Reference number: 200008265
Date of Revision: 08/04/2017
Date Printed: 08/04/2017

LUPEROX® is a registered trademark of Arkema Inc.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids (<http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html>) Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices.

It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use, performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary

Product code: 797000

Version 2.3

Issued on: 08/04/2017

Page: 13 / 14

LUPEROX® DHBP

tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.